

EXHIBIT "C"  
CASE NO. 9232  
ORDER NO. R-8541

<u>OPERATOR, WELL NAME, AND NUMBER</u>	<u>LOCATION</u>
Gulf Oil Corporation Harry Leonard "E" No. 6	1980 FSL & 1980 FEL Section 2, T-21S, R-37E
Shell Western E & P State "2" No. 20	990 FSL & 2300 FWL Section 2, T-21S, R-37E
Shell Western E & P State "2" No. 21	2205 FSL & 988 FWL Section 2, T-21S, R-37E
Shell Western E & P Livingston No. 3	560 FSL & 2030 FEL Section 3, T-21S, R-37E
<i>See attached</i> Shell Western E & P Livingston No. 5	660 FSL & 330 FWL Section 3, T-21S, R-37E
Aztec Dauron No. 3	330 FNL & 990 FEL Section 10, T-21S, R-37E
Humble NM State "V" No. 11	2080 FSL & 2080 FWL Section 10, T-21S, R-37E
Tidewater Oil State "S" No. 6	760 FNL & 1980 FWL Section 15, T-21S, R-37E
Conoco Inc. Lockhart A-27 No. 3	330 FNL & 1650 FWL Section 27, T-21S, R-37E

-5-  
Case No. 9232  
Order No. R-8541

(5) Prior to initiating injection within one-half mile of any of the wells shown on Exhibit "C" attached to this order, the applicant shall present additional calculations, temperature surveys, cement bond logs, or other pertinent information to the supervisor of the Division's district office in Hobbs who, after review of such additional information, may require additional testing, logging, or remedial cement operations to be conducted on the subject wells.

# ATTACHMENT 2

## NORTHEAST DRINKARD UNIT

Lea County, New Mexico

Additional Information for Wells Included in Exhibit "C"

Case No. 9232, Order No. R-8541

<u>Operator &amp; Well</u>	<u>Location</u>	<u>Comments</u>
Chevron Leonard "E" #6 (NEDU No. 221W)	1980'FSL & 1980'FWL 2-21S-37E	TOC at 4085' (Temp Svy). Harry
SWEPI State Sec. 2 #20 No. 317)	990'FSL & 2300'FWL 2-21S-37E	Orig. TOC at 5350'; sqz'd in 12/87 w/ add'l 150 sx; (NEDU TOC now at 4770 (calc).)
SWEPI State Sec. 2 #21 (NEDU No. 312)	2205'FSL & 988'FWL 2-21S-37E	TOC at 3140' (Temp Svy).
SWEPI Livingston #3	560'FSL & 2030'FEL 3-21S-37E	Orig. TOC at 5345'; sqz'd in 12/87 w/ add'l 250 sx; TOC now at 4200' (calc).
SWEPI Livingston #5 (NEDU No. 302)	660'FSL & 330FWL 3-21S-37E	Liner set w/ 400 sx, not 200 sx as orig. reported; TOC at TOL (2964', circ).
Meridian Dauron #3	330'FNL & 990'FEL 10-21S-37E	TOC at 4860' (Temp Svy).
Exxon NM State "V" #11 (NEDU No. 503W)	2080'FSL & 2080'FWL 10-21S-37E	TOC at 2500' (Temp Svy).
Texaco State "S" #6 No. 605W)	760'FNL & 1980'FWL 15-21S-37E	Orig. TOC at 3840 (Temp Svy); Liner tied back to (NEDU sfc in 1977 (TOC @ sfc).
Conoco Lockhart A-27 #3	330'FNL & 1650'FWL 27-21S-37E	Cmt'd w/ 500 sx, not 200 sx as orig. reported; TOC at 5050' (calc).