

Form 9-331a
(March 1942)

(SUBMIT IN TRIPLICATE)

Land Office Las Cruces

Lease No. 032096 (b)

Unit N.M.P.U.

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

RECEIVED

AUG 8 - 1951

U.S. GEOLOGICAL SURVEY
OIL CONSERVATION COMMISSION
HOBBS OFFICE

DUPLICATE
ILLEGIBLE

SUNDRY NOTICES AND REPORTS ON WELLS

| | | | |
|--|-------------------------------------|--|--|
| NOTICE OF INTENTION TO DRILL | <input checked="" type="checkbox"/> | SUBSEQUENT REPORT OF WATER SHUT-OFF | |
| NOTICE OF INTENTION TO CHANGE PLANS | | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING | |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF | | SUBSEQUENT REPORT OF ALTERING CASING | |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL | | SUBSEQUENT REPORT OF REDRILLING OR REPAIR | |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE | | SUBSEQUENT REPORT OF ABANDONMENT | |
| NOTICE OF INTENTION TO PULL OR ALTER CASING | | SUPPLEMENTARY WELL HISTORY | |
| NOTICE OF INTENTION TO ABANDON WELL | | | |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

A. M. Lockhart B-11 No. 3

Hobbs, New Mexico

August 7, 1951

Well No. 2 is located 1980 ft. from N line and 330 ft. from W line of sec. 11

11/4 Sec. 11
(1/4 Sec. and Sec. No.)

21-S
(Twp.)

37-E
(Range)

N.M.P.M.
(Meridian)

Brunson
(Field)

Lee
(County or Subdivision)

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is _____ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

It is our intention to drill a well with rotary tools at the above location to a total depth of approximately 7670', or to a depth sufficient to attempt completion in the Ellenburger horizon. All casing points will be completed in accordance with approved methods of the U.S. Geological Survey and any other special requirements will be complied with.

It is planned to use the following casing pattern: 10 3/4" casing to be set at approximately 250' and cemented with 250 sacks, cement to be circulated to surface; 7 5/8" casing to be set at approximately 3150' and cemented with 1260 sacks, or sufficient cement to protect the salt section; 5 1/2" casing to be set at approximately 7670' and cemented with 525 sacks as determined by survey and to be perforated opposite the pay zone.

Approval to produce this well upon completion is also requested.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Continental Oil Company

Address Box CC

Hobbs, New Mexico

By [Signature]

Title Asst. Dist. Superintendent

STANTON, R. J. 1964