

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYLand Office Las CrucesLease No. 032096 (b)Unit E

1953

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

January 30, 1953

Well No. 1 is located 2310 ft. from N line and 330 ft. from E line of sec. 11W 1/4 Sec. 11
(1/4 Sec. and Sec. No.)21-S
(Twp.)37-E
(Range)N. 31. 1. N.
(Meridian)Drinkard
(Field)Lea
(County or Subdivision)New Mexico
(State or Territory)The elevation of the derrick floor above sea level is 3424 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

It is our intention to drill a well with rotary tools at the above location to a depth of approximately 6700', or to a depth sufficient to complete in the Drinkard Horizon. All casing points will be completed in accordance with approved methods of the U.S. Geological Survey and any other Special Requirements will be complied with.

It is planned to use the following casing pattern, 13 3/8" casing to be set at approximately 250' and cemented with 250 sacks, cement to be circulated to surface, 8 5/8" casing to be set at approximately 3150' and cemented with 1200 sacks, or sufficient cement to protect the salt section; 5 1/2" casing to be set at approximately 6500' and cemented with 400 sacks.

Approval to produce this well upon completion is also requested.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Ross Sears Agent for J. W. RodgersAddress Box 1718Hobbs, New MexicoBy J. W. RodgersTitle J. W. Rodgers - DRILL Operator