



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYLand Office Las Alamos
Lease No. LA 032096 (b)
Unit NEPU

RECEIVED

APR 23 1954

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

A. L. Lockhart B-12 No. 7

Hobbs, New Mexico April 22, 19 54

Well No. 7 is located 330 ft. from N line and 330 ft. from E line of sec. 12
SW/4 Section 12 21-S 37-4 NEPU
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Terry & Blinberry La New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is _____ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work.)

It is intended to drill a well with rotary tools at the above location to a total depth of approximately 5,900'. All casing will be cemented in accordance with approved methods of the U. S. Geological Survey and any other special requirements will be complied with.

It is planned to use the following casing pattern: 10 3/4" casing to be set at approximately 250' and cemented with approximately 250 sacks cement to be circulated to surface; 7 5/8" casing to be set at approximately 3,150' and cemented with approximately 1,045 sacks cement; 5 1/2" casing to be set at approximately 5,900' and cemented with approximately 425 sacks cement, exact amount to be determined by caliper survey. Casing to be perforated opposite the pay zone.

Approval to produce this well upon completion is also requested.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Continental Oil CompanyAddress Box 427Hobbs, New MexicoBy [Signature]Title District Superintendent

