


Form 9-331a
(Feb. 1951)

(SUBMIT IN TRIPLICATE)

 UNITED STATES
 DEPARTMENT OF THE INTERIOR
 GEOLOGICAL SURVEY

 Land Office Las Cruces
 Lease No. 032076 (b)
 Unit N.M.P.U.

RECEIVED

JUL 27 1954

GEOLOGICAL SURVEY
SANTA FE, NEW MEXICO

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	☒	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

A. M. Lockhart B-12 No. 8

Hobbs, New Mexico July 26, 1954

Well No. 8 is located 1980 ft. from N line and 1980 ft. from W line of sec. 12NE 1/4 NW 1/4 Sec. 12
(1/4 Sec. and Sec. No.)213
(Twp.)37E
(Range)N.M.P.U.
(Meridian)Terry Hinesbry
(Field)1m
(County or Subdivision)New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

It is our intention to drill a well with rotary tools at the above location to a total depth of approximately 5,900', or to a depth sufficient for completion in the Hinesbry formation. All casing will be cemented in accordance with approved methods of the U. S. Geological Survey and any other special requirements will be complied with.

It is planned to use the following casing patterns: 10 3/4" casing to be set at approximately 250' and cemented with 250 sacks cement, cement to be circulated to surface; 7 5/8" casing to be set at approximately 3150' and cemented with 1,045 sacks, or sufficient cement to protect the salt section; 5 1/2" casing to be set at total depth and cemented with 415 sacks or the required amount as determined by Caliper survey, casing to be perforated opposite the pay zone.

Approval to produce this well upon completion is also requested.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Continental Oil CompanyAddress Box 427Hobbs, New MexicoBy [Signature]Title District Superintendent

ILLEGIBLE

