NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS 9

JICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is comp

7

nstructions in the Rules and Regulations of th	Commission.	ed by an agent of the Commission. See	
]	indicate Nature of Report by Checking B	SEIUW	1
REPORT ON BEGINNING DRILLING OPERATIONS	REPORT ON RESULT OF TEST OF CASING SHUT-OFF	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL	REPORT ON RECOMPLETION OPERATION	REPORT ON (Other) ACID PRACTURE	x
	February 7, 1955	Hobbs, New Hexico	······································
Following is a report on the work done	and the results obtained under the heading	g noted above at the	
mall All Comment		luslee	
(Company or Operator) (Contractor)	, Well No 1	(Lease) in the	12 ,
(Contractor)	rry-Blinebry Pool,	Lea	County.
The Dates of this work were as folows:	January 23, 1955		
Notice of intention to do the work (was) (wa	s not) submitted on Form C-102 on	(Cross out incorrect words)	, 19,
and approval of the proposed plan (was) (wa	s not) obtained.		
	ACCOUNT OF WORK DONE AND RE		
Treated thru casing perform the contains	erforations 5750'-5870' with ing 18 sand per gallon.	15,000 gallons acid Petro-	
Treated thru casing perform (Dovell) contains	erforations 5750 -5870 with	15,000 gallons acid Petro-	
Treated thru casing po Frac (Dowell) contains	erforations 5750'-5870' with ing 18 sand per gallon.	15,000 gallons acid Petro-	
Treated thru casing po Frac (Dowell) contains	erforations 5750'-5870' with ing 18 sand per gallon.	15,000 gallons acid Petro-	
Treated thru casing po Frac (Dowell) contains	erforations 5750'-5870' with ing 18 sand per gallon.	15,000 gallons acid Petro-	
Treated thru casing po Frac (Dowell) contains	erforations 5750'-5870' with ing 18 sand per gallon.	15,000 gallons acid Petro-	
Treated thru casing po Frac (Dowell) contains	erforations 5750'-5870' with ing 18 sand per gallon.	15,000 gallons acid Petro-	
Treated thru casing po Frac (Dovell) contains	erforations 5750'-5870' with ing 18 sand per gallon.	15,000 gallons acid Petro- choke. CP packer. PTP 75	p ei.
Treated thru casing portrac (Dowell) contains On OPT flowed 97 BOPD GOR 1649.	erforations 5750'-5870' with ing 18 sand per gallon. cut 18 water thru 30/64" of the sand per gallon.	15.000 gallons acid Petro- choke. CP packer. FTP 75 p	p ei.
Treated thru casing po Frac (Dovell) contains	erforations 5750'-5870' with ing 18 sand per gallon. out 18 water thru 30/64" o	15,000 gallons acid Petro- thoke. CP packer. FTP 75	p ei.
Treated thru casing portrac (Dovell) contains On OPT flowed 97 BOPD GOR 1649. Witnessed by Ha B. Leach (Name)	Shell Oil Company (Company)	Production Fore (Title) y that the information given above is true a	net complet
Treated thru casing portrac (Dowell) contains On OFT flowed 97 BOPD GOR 1649. Witnessed by E. B. Leach (Name)	Shell Oil Company (Company) I hereby certiful to the besOption.	Production Fore (Title) y that the information given above is true a syndrographic by B. Nevill B. Nevill	man und complet
Treated thru casing portrac (Dowell) contains On OPT flowed 97 BOPD GOR 1649. Witnessed by Ha B. Learh (Name)	Shell Oil Company (Company) I hereby certiful to the besOption.	Production Fore (Title) y that the information given above is true a small straightful by B. Nevill Vision Exploitation Engineer	man und complet
Treated thru casing portrac (Dovell) contains On Orf flowed 97 BOPD GOR 1649. Witnessed by H. B. Learh (Name)	Shell Oil Company (Company) I hereby certiful to the besOption Name	Production Fore (Title) y that the information given above is true as makes with the information given above is true as makes with the information of the informati	man und complet