Form 3160-5	UNITED STATES DEPARTMENT OF THE INTERIOR					ns. Divi s i		
(August 1999)		NAGEMENT		I. French Dr. Expires: November 30, 2000				
				Hobbs,	NM -	88240 iai No.		
	-	RY NOTICES AND REI				LC-032096B		
		Do not use this form for proposals to drill or to re-enter a				6. If Indian, Allotee or Tribe Name		
	· · · · ·	ed well. Use Form 3160-3 (a section and the section of the sec				<u> </u>	
1. T	SUBMIT IN	TRIPLICATE - Other	r instructions on rever.	se side		7. If Unit or CA/	Agreement, Nam	ne and/or No
 Type of Well Oil We 	il 🗌 Gas Well	☑ Other INJ	ECTION			8. Well Name an	d No.	
2. Name of Operate	or					LOCKHAR	T B-13A #	4
APACHE CC	RPORATION		·····			9. API Well No.		
3a. Address			3b. Phone No. (incl			30-025-065		
		500 TULSA, OK 741	36-4224 918-491	1-4957		10. Field and Po		y Area
	1 (Footage, Sec., T, R, M, TO S D 27E 108		пти			SAN AND		
SEC. 13, T21S-R37E 1980' FSL, 1980' FWL UNIT			NII K			11. County or Pa LEA COUN	-	
12		PROPRIATE BOX(s) TO		F NOTICE F	EPORT (
	F SUBMISSION			TYPE OF			· . 1 · .	
		Acidize				Pacuma)		
Notice of	Intent	Alter Casing		Production (Start/F		Resume) Uwater Shut-Off		
Subseque	nt Report	Casing Repair	New Construction	Recomp		☑ Other		CO,
Final Abar	ndonment Notice	Change Plans	Plug and Abandon	Tempor	arily Aban	don		r, ACIE
		Convert to Injection	Plugback	🗌 Water D	Disposal		REPL.	ACE TI
Attach the Bo following com testing has be	I is to deepen directiona and under which the work opletion of the involved op sen completed. Final Ab nat the site is ready for fir	will be performed or provide the perations. If the operation result andonment Notices shall be filled to the filled operation of the filled operation operat	he Bond No. on file with BLM/ lits in a multiple completion or ed only after all requirements,	BIA. Required s recompletion ir including reclari	ubsequent a new inter nation, have	reports shall be fi val, a Form 3160	-4 shall be filed	ays I once
If the proposa Attach the Bo following com testing has be determined th	I is to deepen directiona and under which the work spletion of the involved of een completed. Final Ab hat the site is ready for fir Test anchors. M DO & CO. Tag pkr to 4423'. Se	will be performed or provide the perations. If the operation result andonment Notices shall be file hal inspection.) IIRU SU. Rel pkr & pol @ 4683'. Clean to PBC t pkr & test csg @ 500#	he Bond No. on file with BLM/ lits in a multiple completion or ed only after all requirements, h w/ 143 jts 2 3/8" J-55 FD @ 5130'. POH w/ s	BIA. Required s recompletion ir including reclar 5 IPC tbg. S shoe & WP.	ubsequent a new inter nation, have DFWE. RIH w/	reports shall be fi val, a Form 3160 been completed csg scraper to	-4 shall be filed , and the opera 0 4500'. RI	ays I once Itor has H w/
If the proposa Attach the Bo following com testing has be determined th 01/11/02 01/14/02-	I is to deepen directiona and under which the work spletion of the involved of een completed. Final Ab hat the site is ready for fir Test anchors. M DO & CO. Tag pkr to 4423'. Se 4" liner 1/24/01.	will be performed or provide the perations. If the operation result andonment Notices shall be file hal inspection.) IIRU SU. Rel pkr & pol @ 4683'. Clean to PBC t pkr & test csg @ 500#	he Bond No. on file with BLM/ uts in a multiple completion or ed only after all requirements, h w/ 143 jts 2 3/8" J-55 FD @ 5130'. POH w/ s ¢ for 15 mins. Est inj r	BIA. Required s recompletion ir including reclard DIPC tbg. S shoe & WP. ate down tbg	a new inter nation, have DFWE. RIH w/ g of 2 1/2	reports shall be fi val, a Form 3160 been completed csg scraper to bpm & 1000	-4 shall be filed , and the opera o 4500'. RI 0#. Prep to	ays I once Itor has H w/ run
If the proposa Attach the Bo following com testing has be determined th 01/11/02 01/14/02- 01/22/02	I is to deepen directiona and under which the work opletion of the involved op- een completed. Final Ab- hat the site is ready for fir Test anchors. M DO & CO. Tag pkr to 4423'. Se 4" liner 1/24/01. Tag fill @ 4780' RU BJ. Pump 2	will be performed or provide the perations. If the operation result andonment Notices shall be fil- hal inspection.) IIRU SU. Rel pkr & pol @ 4683'. Clean to PBC at pkr & test csg @ 500# SDFN.	he Bond No. on file with BLM/ lts in a multiple completion or ed only after all requirements, h w/ 143 jts 2 3/8" J-55 FD @ 5130'. POH w/ s f for 15 mins. Est inj r 0'. POH. RIH w/ 4" flu Cmt 4" csg in 5 1/2" p	BIA. Required s recompletion ir including reclam 5 IPC tbg. S shoe & WP. ate down tbg ush jt liner.	ubsequent a new inter nation, have DFWE. RIH w/ g of 2 1/2 Set shoe	reports shall be fi val, a Form 3160 been completed csg scraper to bpm & 1000 @ 5126', top	-4 shall be filed , and the opera o 4500'. RI)#. Prep to of hanger (ays I once Itor has H w/ run @ 4457'
If the proposa Attach the Bo following com testing has be determined th 01/11/02 01/14/02- 01/22/02	I is to deepen directiona and under which the work spletion of the involved op een completed. Final Ab hat the site is ready for fir Test anchors. M DO & CO. Tag pkr to 4423'. Se 4" liner 1/24/01. Tag fill @ 4780' RU BJ. Pump 2 Flush w/ 33 BFV RIH w/ 4 3/4" bi	will be performed or provide the perations. If the operation result and onment Notices shall be file hal inspection.) IIRU SU. Rel pkr & pol @ 4683'. Clean to PBC the pkr & test csg @ 500# SDFN. Mill to PBTD @ 513 0 BW to establish rate.	he Bond No. on file with BLM/ lts in a multiple completion or ed only after all requirements, h w/ 143 jts 2 3/8" J-55 ID @ 5130'. POH w/ s f for 15 mins. Est inj r 0'. POH. RIH w/ 4" flu Cmt 4" csg in 5 1/2" p H. SDFWE. p of liner @ 4457'. PC	BIA. Required s recompletion ir including reclam 5 IPC tbg. S shoe & WP. ate down tbg ush jt liner. prod csg w/ 3 DH. RIH w/	ubsequent a new inter nation, have DFWE. RIH w/ g of 2 1/2 Set shoe 30 sx Cla 3 1/4" bi	reports shall be fi val, a Form 3160 been completed csg scraper to bpm & 1000 @ 5126', top ss C neat cmt t on 2 1/16" t	-4 shall be filed , and the opera o 4500'. RI)#. Prep to of hanger (a @ 2 BPM	ays once tor has H w/ run @ 4457'. & 540#.
If the proposa Attach the Bo following com testing has be determined th 01/11/02 01/14/02- 01/22/02 01/22/02	I is to deepen directiona and under which the work opletion of the involved op- een completed. Final Ab- hat the site is ready for fir Test anchors. M DO & CO. Tag pkr to 4423'. Se 4" liner 1/24/01. Tag fill @ 4780' RU BJ. Pump 2 Flush w/ 33 BFV RIH w/ 4 3/4" bi 5086'. DO float RU Computalog	will be performed or provide the performed or provide the performed or provide the performed of performed or provide the performed of the performed and onment Notices shall be file and inspection.) IIRU SU. Rel pkr & pol @ 4683'. Clean to PBT @ 4683'. Clean to PBT the pkr & test csg @ 500# SDFN. . Mill to PBTD @ 513 0 BW to establish rate. W. Rel from liner. POH it on 2 7/8" tbg. Tag to collar & cmt to 5123'. . RIH w/ 2 1/2" gun &	he Bond No. on file with BLM/ lts in a multiple completion or ed only after all requirements, h w/ 143 jts 2 3/8" J-55 FD @ 5130'. POH w/ s f for 15 mins. Est inj r 0'. POH. RIH w/ 4" flu Cmt 4" csg in 5 1/2" p H. SDFWE. p of liner @ 4457'. PC Circ well clean. POH. perf San Andres interv	BIA. Required s recompletion ir including reclard 5 IPC tbg. S shoe & WP. rate down tbg ush jt liner. prod csg w/ 3 DH. RIH w/ Prep to per val @ 4505-3	ubsequent a new inter nation, have DFWE. RIH w/ g of 2 1/2 Set shoe 30 sx Cla 3 1/4" bi f & acidi 35', 4608	reports shall be fi val, a Form 3160 been completed csg scraper to bpm & 1000 @ 5126', top ss C neat cmt t on 2 1/16" t ze. SDFN. -15', 4628-50	-4 shall be filed , and the opera 0 4500'. RI 0#. Prep to 0 f hanger (2 BPM bg. Tag flo 0', 4690-97',	ays once tor has H w/ run @ 4457' & 540# pat colla: , 4755-9
If the proposa Attach the Bo following com testing has be determined th 01/11/02 01/14/02- 01/22/02 01/22/02 01/24/02	I is to deepen directiona and under which the work opletion of the involved op- een completed. Final Ab- hat the site is ready for fir Test anchors. M DO & CO. Tag pkr to 4423'. Se 4" liner 1/24/01. Tag fill @ 4780' RU BJ. Pump 2 Flush w/ 33 BFV RIH w/ 4 3/4" bi 5086'. DO float RU Computalog 4960-72', 4992-:	will be performed or provide the performed or provide the performed or provide the performed of performed or provide the and onment Notices shall be file all inspection.) IIRU SU. Rel pkr & pol @ 4683'. Clean to PBC @ 4683'. Clean to PBC # pkr & test csg @ 500# SDFN. Mill to PBTD @ 513 0 BW to establish rate. W. Rel from liner. POH it on 2 7/8" tbg. Tag to collar & cmt to 5123'.	he Bond No. on file with BLM/ lts in a multiple completion or ed only after all requirements, h w/ 143 jts 2 3/8" J-55 FD @ 5130'. POH w/ s f for 15 mins. Est inj r 0'. POH. RIH w/ 4" flu Cmt 4" csg in 5 1/2" p H. SDFWE. p of liner @ 4457'. PC Circ well clean. POH. perf San Andres interv 50', 5100-10'. RD Com	BIA. Required s recompletion ir including reclard 5 IPC tbg. S shoe & WP. ate down tbg ush jt liner. prod csg w/ 3 OH. RIH w/ Prep to per: val @ 4505-3 uputalog. RI	ubsequent a new inter nation, have DFWE. RIH w/ g of 2 1/2 Set shoe 30 sx Cla 3 1/4" bi f & acidi 35', 4608 H w/ pkr	reports shall be fival, a Form 3160 been completed csg scraper to bbpm & 1000 @ 5126', top ss C neat cmt t on 2 1/16" t ze. SDFN. -15', 4628-50 o on 2 7/8 " tb	-4 shall be filed , and the opera 0 4500'. RI)#. Prep to 0 f hanger (a @ 2 BPM bg. Tag flo 0', 4690-97', 9g set pkr @	ays once tor has H w/ run @ 4457'. & 540#. pat collar , 4755-9) 4423'.
If the proposa Attach the Bo following com testing has be determined th 01/11/02 01/14/02- 01/22/02 01/22/02 01/28/02 01/28/02 01/29/02	I is to deepen directiona ind under which the work opletion of the involved op- een completed. Final Ab- hat the site is ready for fir Test anchors. M DO & CO. Tag pkr to 4423'. Se 4" liner 1/24/01. Tag fill @ 4780' RU BJ. Pump 2 Flush w/ 33 BFV RIH w/ 4 3/4" bi 5086'. DO float RU Computalog 4960-72', 4992- Acidize interval	 will be performed or provide the performed or provide the performed or provide the performed on provide the performed on provide the performed on performance of the performanc	he Bond No. on file with BLM/ lts in a multiple completion or ed only after all requirements, h w/ 143 jts 2 3/8" J-55 FD @ 5130'. POH w/ s f for 15 mins. Est inj r 0'. POH. RIH w/ 4" flu Cmt 4" csg in 5 1/2" p H. SDFWE. p of liner @ 4457'. PC Circ well clean. POH. perf San Andres interv 50', 5100-10'. RD Com	BIA. Required s recompletion ir including reclard 5 IPC tbg. S shoe & WP. ate down tbg ush jt liner. prod csg w/ 3 OH. RIH w/ Prep to per: val @ 4505-3 uputalog. RI	ubsequent a new inter nation, have DFWE. RIH w/ g of 2 1/2 Set shoe 30 sx Cla 3 1/4" bi f & acidi 35', 4608 H w/ pkr	reports shall be fival, a Form 3160 been completed csg scraper to bbpm & 1000 @ 5126', top ss C neat cmt t on 2 1/16" t ze. SDFN. -15', 4628-50 o on 2 7/8 " tb	-4 shall be filed , and the opera o 4500'. RI)#. Prep to of hanger (a @ 2 BPM bg. Tag flo bg. Tag flo o', 4690-97', og set pkr @ 'P. (Contir	ays i once itor has H w/ run @ 4457'. & 540#. pat collar , 4755-9 9 4423'. nued on l
If the proposa Attach the Bo following com testing has be determined th 01/11/02 01/14/02- 01/22/02 01/24/02 01/28/02 01/28/02 01/29/02	I is to deepen directiona and under which the work opletion of the involved op- een completed. Final Ab- hat the site is ready for fir Test anchors. M DO & CO. Tag pkr to 4423'. Se 4" liner 1/24/01. Tag fill @ 4780' RU BJ. Pump 2 Flush w/ 33 BFV RIH w/ 4 3/4" bi 5086'. DO float RU Computalog 4960-72', 4992-1 Acidize interval	 will be performed or provide the performed or provide the performed or provide the performed on provide the performed on provide the performed on performance of the performanc	he Bond No. on file with BLM/ lits in a multiple completion or ed only after all requirements, h w/ 143 jts 2 3/8" J-55 FD @ 5130'. POH w/ s f for 15 mins. Est inj r 0'. POH. RIH w/ 4" flu Cmt 4" csg in 5 1/2" p H. SDFWE. p of liner @ 4457'. PC Circ well clean. POH. perf San Andres interv 50', 5100-10'. RD Com DX HCL diverted w/ 10	BIA. Required s recompletion ir including reclard 5 IPC tbg. S shoe & WP. ate down tbg ush jt liner. prod csg w/ 3 OH. RIH w/ Prep to per: val @ 4505-3 uputalog. RI	ubsequent a new inter nation, have DFWE. RIH w/ g of 2 1/2 Set shoe 30 sx Cla 3 1/4" bi f & acidi 35', 4608 H w/ pkr 5.5 BPM	reports shall be fival, a Form 3160 been completed csg scraper to bbpm & 1000 @ 5126', top ss C neat cmt t on 2 1/16" t ze. SDFN. -15', 4628-50 f on 2 7/8 " tb & 2500# AT	-4 shall be filed , and the opera o 4500'. RI)#. Prep to of hanger (a @ 2 BPM bg. Tag flo bg. Tag flo)', 4690-97', og set pkr @ 'P. (Contin	ays i once itor has H w/ run @ 4457'. & 540#. pat collar , 4755-9 9 4423'. nued on l
If the proposa Attach the Bo following com testing has be determined th 01/11/02 01/14/02- 01/22/02 01/22/02 01/28/02 01/28/02 01/29/02	I is to deepen directiona ind under which the work opletion of the involved op- een completed. Final Ab- hat the site is ready for fir Test anchors. M DO & CO. Tag pkr to 4423'. Se 4" liner 1/24/01. Tag fill @ 4780' RU BJ. Pump 2 Flush w/ 33 BFV RIH w/ 4 3/4" bi 5086'. DO float RU Computalog 4960-72', 4992- Acidize interval	 will be performed or provide the performed or provide the performed or provide the performed on provide the performed on provide the performed on performance of the performanc	he Bond No. on file with BLM/ lits in a multiple completion or ed only after all requirements, h w/ 143 jts 2 3/8" J-55 FD @ 5130'. POH w/ s f for 15 mins. Est inj r 0'. POH. RIH w/ 4" flu Cmt 4" csg in 5 1/2" p H. SDFWE. p of liner @ 4457'. PC Circ well clean. POH. perf San Andres interv 50', 5100-10'. RD Com DX HCL diverted w/ 10 Title	BIA. Required s recompletion ir including reclard 5 IPC tbg. S shoe & WP. ate down tbg ush jt liner. prod csg w/ 3 OH. RIH w/ Prep to per: val @ 4505-3 uputalog. RI	ubsequent a new inter nation, have DFWE. RIH w/ g of 2 1/2 Set shoe 30 sx Cla 3 1/4" bi f & acidi 35', 4608 H w/ pkr 5.5 BPM	reports shall be fival, a Form 3160 been completed csg scraper to bpm & 1000 @ 5126', top ss C neat cmf t on 2 1/16" t ze. SDFN. -15', 4628-50 on 2 7/8 " tb & 2500# AT neering Tech	-4 shall be filed , and the opera o 4500'. RI)#. Prep to of hanger (a @ 2 BPM bg. Tag flo bg. Tag flo)', 4690-97', og set pkr @ 'P. (Contin	ays i once itor has H w/ run @ 4457'. & 540#. pat collar , 4755-9 9 4423'. nued on l
If the proposa Attach the Bo following com testing has be determined th 01/11/02 01/14/02- 01/22/02 01/24/02 01/28/02 01/28/02 14. I hereby certify Name (<i>Printed</i>	I is to deepen directiona and under which the work opletion of the involved op- een completed. Final Ab- hat the site is ready for fir Test anchors. M DO & CO. Tag pkr to 4423'. Se 4" liner 1/24/01. Tag fill @ 4780' RU BJ. Pump 2 Flush w/ 33 BFV RIH w/ 4 3/4" bi 5086'. DO float RU Computalog 4960-72', 4992-1 Acidize interval	will be performed or provide the perations. If the operation result and onment Notices shall be file that inspection.) IIRU SU. Rel pkr & poll (a) 4683'. Clean to PB') (a) 4683'. Clean to PB') (b) 4683'. Clean to PB') (c) 4683'. Clean to PB') (c) 4683'. Clean to PB') (c) 4683'. Clean to PB') (c) 507'. SDFN. (c) Mill to PBTD (a) 513 (c) 80' to establish rate. (c) 80' to establish ra	he Bond No. on file with BLM/ lts in a multiple completion or ed only after all requirements, h w/ 143 jts 2 3/8" J-55 FD @ 5130'. POH w/ s f for 15 mins. Est inj r 0'. POH. RIH w/ 4" flu Cmt 4" csg in 5 1/2" p H. SDFWE. p of liner @ 4457'. PC Circ well clean. POH. perf San Andres interv 50', 5100-10'. RD Com DX HCL diverted w/ 10 Title Date	BIA. Required s recompletion ir including reclard 5 IPC tbg. S shoe & WP. rate down tbg ush jt liner. prod csg w/ 3 0H. RIH w/ Prep to per val @ 4505-3 uputalog. RI 000# RS @ 0	ubsequent a new inter nation, have DFWE. RIH w/ g of 2 1/2 Set shoe 30 sx Cla 3 1/4" bi f & acidi 35', 4608 H w/ pkr 5.5 BPM Sr. Engi	reports shall be fival, a Form 3160 been completed csg scraper to bbpm & 1000 @ 5126', top ss C neat cmt t on 2 1/16" t ze. SDFN. -15', 4628-50 f on 2 7/8 " tb & 2500# AT	-4 shall be filed , and the opera o 4500'. RI)#. Prep to of hanger (a @ 2 BPM bg. Tag flo bg. Tag flo)', 4690-97', og set pkr @ 'P. (Contin	ays i once itor has H w/ run @ 4457'. & 540#. pat collar , 4755-9 9 4423'. nued on l
If the proposa Attach the Bo following com testing has be determined th 01/11/02 01/14/02- 01/22/02 01/24/02 01/28/02 01/28/02 14. I hereby certify Name (Printed Signature	I is to deepen directiona and under which the work spletion of the involved op een completed. Final Ab hat the site is ready for fir Test anchors. M DO & CO. Tag pkr to 4423'. Se 4" liner 1/24/01. Tag fill @ 4780' RU BJ. Pump 2 Flush w/ 33 BFV RIH w/ 4 3/4" bi 5086'. DO float RU Computalog 4960-72', 4992- Acidize interval	will be performed or provide the perations. If the operation result and onment Notices shall be file all inspection.) IIRU SU. Rel pkr & pol @ 4683'. Clean to PBC the pkr & test csg @ 500# SDFN. . Mill to PBTD @ 513 0 BW to establish rate. W. Rel from liner. POH it on 2 7/8" tbg. Tag to collar & cmt to 5123'. . RIH w/ 2 1/2" gun & 5004', 5020-32', 5045-6 w/ 4000 gals 15% BXI and correct	he Bond No. on file with BLM/ lits in a multiple completion or ed only after all requirements, h w/ 143 jts 2 3/8" J-55 FD @ 5130'. POH w/ s f for 15 mins. Est inj r 0'. POH. RIH w/ 4" flu Cmt 4" csg in 5 1/2" p H. SDFWE. p of liner @ 4457'. PC Circ well clean. POH. perf San Andres interv 50', 5100-10'. RD Com DX HCL diverted w/ 10 Title	BIA. Required s recompletion ir including reclard 5 IPC tbg. S shoe & WP. rate down tbg ush jt liner. prod csg w/ 3 0H. RIH w/ Prep to per val @ 4505-3 uputalog. RI 000# RS @ 0	ubsequent a new inter nation, have DFWE. RIH w/ g of 2 1/2 Set shoe 30 sx Cla 3 1/4" bi f & acidi 35', 4608 H w/ pkr 5.5 BPM Sr. Engi	reports shall be fival, a Form 3160 been completed csg scraper to bpm & 1000 @ 5126', top ss C neat cmt t on 2 1/16" t ze. SDFN. -15', 4628-50 on 2 7/8 " th & 2500# AT neering Tech 8/19/2002	-4 shall be filed , and the opera o 4500'. RI)#. Prep to of hanger (a @ 2 BPM bg. Tag flo bg. Tag flo)', 4690-97', og set pkr @ 'P. (Contin	ays ionce itor has H w/ run @ 4457'. & 540#. pat collar , 4755-9 9 4423'. nued on l
If the proposa Attach the Bo following com testing has be determined th 01/11/02 01/14/02- 01/22/02 01/24/02 01/28/02 01/28/02 14. I hereby certify Name (Printed Signature	I is to deepen directiona and under which the work spletion of the involved op een completed. Final Ab hat the site is ready for fir Test anchors. M DO & CO. Tag pkr to 4423'. Se 4" liner 1/24/01. Tag fill @ 4780' RU BJ. Pump 2 Flush w/ 33 BFV RIH w/ 4 3/4" bi 5086'. DO float RU Computalog 4960-72', 4992- Acidize interval	will be performed or provide the perations. If the operation result and onment Notices shall be file all inspection.) IIRU SU. Rel pkr & pol @ 4683'. Clean to PBC the pkr & test csg @ 500# SDFN. . Mill to PBTD @ 513 0 BW to establish rate. W. Rel from liner. POH it on 2 7/8" tbg. Tag to collar & cmt to 5123'. . RIH w/ 2 1/2" gun & 5004', 5020-32', 5045-6 w/ 4000 gals 15% BXI and correct	he Bond No. on file with BLM/ lts in a multiple completion or ed only after all requirements, h w/ 143 jts 2 3/8" J-55 FD @ 5130'. POH w/ s f for 15 mins. Est inj r 0'. POH. RIH w/ 4" flu Cmt 4" csg in 5 1/2" p H. SDFWE. p of liner @ 4457'. PC Circ well clean. POH. perf San Andres interv 50', 5100-10'. RD Com DX HCL diverted w/ 10 Title Date	BIA. Required s recompletion ir including reclard 5 IPC tbg. S shoe & WP. rate down tbg ush jt liner. prod csg w/ 3 0H. RIH w/ Prep to per val @ 4505-3 uputalog. RI 000# RS @ 0	ubsequent a new inter nation, have DFWE. RIH w/ g of 2 1/2 Set shoe 30 sx Cla 3 1/4" bi f & acidi 35', 4608 H w/ pkr 5.5 BPM Sr. Engi	reports shall be fival, a Form 3160 been completed csg scraper to bpm & 1000 @ 5126', top ss C neat cmf t on 2 1/16" t ze. SDFN. -15', 4628-50 on 2 7/8 " tb & 2500# AT neering Tech	-4 shall be filed , and the opera o 4500'. RI)#. Prep to of hanger (a @ 2 BPM bg. Tag flo bg. Tag flo)', 4690-97', og set pkr @ 'P. (Contin	ays ionce itor has H w/ run @ 4457'. & 540#. pat collar , 4755-9 9 4423'. nued on l
If the proposa Attach the Bo following com testing has be determined th 01/11/02 01/14/02- 01/22/02 01/24/02 01/28/02 01/28/02 14. I hereby certify Name (Printed Kit Signature	I is to deepen directiona and under which the work opletion of the involved op- een completed. Final Ab- hat the site is ready for fir Test anchors. M DO & CO. Tag pkr to 4423'. Se 4" liner 1/24/01. Tag fill @ 4780' RU BJ. Pump 2 Flush w/ 33 BFV RIH w/ 4 3/4" bi 5086'. DO float RU Computalog 4960-72', 4992- Acidize interval (Typed) ara Coday	will be performed or provide the perations. If the operation result and onment Notices shall be file that inspection.) IIRU SU. Rel pkr & poll (a) 4683'. Clean to PB') (a) 4683'. Clean to PB') (b) 4683'. Clean to PB') (c) 4683'. Clean to PB') (c) 4683'. Clean to PB') (c) 4683'. Clean to PB') (c) 5020-32' (c) 513 (c) 7/8" tbg. Tag to construct to 5123'. (c) RIH w/ 2 1/2" gun & 5004', 5020-32', 5045-6 (c) W/ 4000 gals 15% BXI (c) FC FF) (c) FR. GLASS	he Bond No. on file with BLM/ lits in a multiple completion or ed only after all requirements, h w/ 143 jts 2 3/8" J-55 FD @ 5130'. POH w/ s f for 15 mins. Est inj r 0'. POH. RIH w/ 4" flu Cmt 4" csg in 5 1/2" p H. SDFWE. p of liner @ 4457'. PC Circ well clean. POH. perf San Andres interv 50', 5100-10'. RD Com DX HCL diverted w/ 10 Title Cor FEDERAL OR ST Title	BIA. Required s recompletion ir including reclard 5 IPC tbg. S shoe & WP. rate down tbg ush jt liner. prod csg w/ 3 0H. RIH w/ Prep to per val @ 4505-3 uputalog. RI 000# RS @ 0	ubsequent a new inter nation, have DFWE. RIH w/ g of 2 1/2 Set shoe 30 sx Cla 3 1/4" bi f & acidi 35', 4608 H w/ pkr 5.5 BPM Sr. Engi	reports shall be fival, a Form 3160 been completed csg scraper to bpm & 1000 @ 5126', top ss C neat cmt t on 2 1/16" t ze. SDFN. -15', 4628-50 on 2 7/8 " th & 2500# AT neering Tech 8/19/2002	4 shall be filed , and the operation of 4500'. RI)#. Prep to of hanger (a @ 2 BPM bg. Tag flo 0', 4690-97', og set pkr @ P. (Contin P. (Contin Date free for	ays ionce itor has H w/ run @ 4457'. & 540#. oat collar , 4755-9 9 4423'. nued on 1 9_{20}_{27} .
If the proposa Attach the Bo following com testing has be determined th 01/11/02 01/14/02- 01/22/02 01/24/02 01/28/02 01/28/02 01/29/02 14. I hereby certify Name (Printed Ki Signature	I is to deepen directiona and under which the work opletion of the involved op- een completed. Final Ab- hat the site is ready for fir Test anchors. M DO & CO. Tag pkr to 4423'. Se 4" liner 1/24/01. Tag fill @ 4780' RU BJ. Pump 2 Flush w/ 33 BFV RIH w/ 4 3/4" bi 5086'. DO float RU Computalog 4960-72', 4992- Acidize interval ruhat the foregoing is true of (Typed) ara Coday	will be performed or provide the perations. If the operation result and onment Notices shall be file that inspection.) IIRU SU. Rel pkr & poll (a) 4683'. Clean to PB' (b) 4683'. Clean to PB' (c) 4683'. Clean to PB' (c) 4683'. Clean to PB' (c) 5075. (c) Mill to PBTD (a) 513 (c) BW to establish rate. W. Rel from liner. POH (c) 6123'. (c) RIH w/ 2 1/2" gun & (c)	he Bond No. on file with BLM/ lts in a multiple completion or ed only after all requirements, h w/ 143 jts 2 3/8" J-55 FD @ 5130'. POH w/ s f for 15 mins. Est inj r 0'. POH. RIH w/ 4" flu Cmt 4" csg in 5 1/2" p H. SDFWE. p of liner @ 4457'. PC Circ well clean. POH. perf San Andres interv 50', 5100-10'. RD Com DX HCL diverted w/ 10 Title Date COR FEDERAL OR ST.	BIA. Required s recompletion ir including reclard 5 IPC tbg. S shoe & WP. rate down tbg ush jt liner. prod csg w/ 3 0H. RIH w/ Prep to per val @ 4505-3 uputalog. RI 000# RS @ 0	ubsequent a new inter nation, have DFWE. RIH w/ g of 2 1/2 Set shoe 30 sx Cla 3 1/4" bi f & acidi 35', 4608 H w/ pkr 5.5 BPM Sr. Engi	reports shall be fival, a Form 3160 been completed csg scraper to bpm & 1000 @ 5126', top ss C neat cmt t on 2 1/16" t ze. SDFN. -15', 4628-50 on 2 7/8 " tb & 2500# AT neering Tech 8/19/2002	4 shall be filed , and the operation of 4500'. RI)#. Prep to of hanger (a @ 2 BPM bg. Tag flo 0', 4690-97', og set pkr @ P. (Contin P. (Contin Date free for	ays ionce itor has H w/ run @ 4457'. & 540#. pat collar , 4755-9 9 4423'. nued on I
If the proposa Attach the Bo following com testing has be determined th 01/11/02 01/14/02- 01/22/02 01/24/02 01/28/02 01/28/02 01/29/02 14. I hereby certify Name (Printed Kit Signature Approved by Conditions of approx certify that the applica certify that the applica	I is to deepen directiona and under which the work spletion of the involved op een completed. Final Ab hat the site is ready for fir Test anchors. M DO & CO. Tag pkr to 4423'. Se 4" liner 1/24/01. Tag fill @ 4780' RU BJ. Pump 2 Flush w/ 33 BFV RIH w/ 4 3/4" bi 5086'. DO float RU Computalog 4960-72', 4992- Acidize interval What the foregoing is true of that the foregoing is true of CEPTEDIO ORIG. SGD.) D	will be performed or provide the perations. If the operation result and onment Notices shall be file that inspection.) IIRU SU. Rel pkr & poll (a) 4683'. Clean to PB' (b) 4683'. Clean to PB' (c) 4683'. Clean to PB' (c) 4683'. Clean to PB' (c) 5075. (c) Mill to PBTD (a) 513 (c) BW to establish rate. W. Rel from liner. POH (c) 6123'. (c) RIH w/ 2 1/2" gun & (c)	he Bond No. on file with BLM/ lits in a multiple completion or ed only after all requirements, h w/ 143 jts 2 3/8" J-55 FD @ 5130'. POH w/ 9 \$ for 15 mins. Est inj r 0'. POH. RIH w/ 4" flu Cmt 4" csg in 5 1/2" p H. SDFWE. p of liner @ 4457'. PC Circ well clean. POH. perf San Andres interv 50', 5100-10'. RD Com DX HCL diverted w/ 10 Title Date FOR FEDERAL OR ST Title Cffice	BIA. Required s recompletion ir including reclard 5 IPC tbg. S shoe & WP. ate down tbg ush jt liner. orod csg w/ 3 OH. RIH w/ Prep to per val @ 4505- aputalog. RI 000# RS @ 0 ATE OFFIC	ubsequent a new inter nation, have DFWE. RIH w/ g of 2 1/2 Set shoe 30 sx Cla 3 1/4" bi f & acidi 35', 4608 H w/ pkr 6.5 BPM Sr. Engi E USE	reports shall be fival, a Form 3160 been completed csg scraper to bpm & 1000 @ 5126', top ss C neat cmt t on 2 1/16" t ze. SDFN. -15', 4628-50 on 2 7/8 " th & 2500# AT neering Tech 8/19/2002	-4 shall be filed , and the operation of 4500'. RI D#. Prep to of hanger (a @ 2 BPM bg. Tag flo bg. Tag flo bg. Tag flo o', 4690-97', og set pkr @ 'P. (Contin infician	ays increases iter has H w/ run @ 4457'. @ 4457'. @ 4457'. @ 4457'. pat collar

which would entrie the applicant to contract operations meteor.		يك
Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency	of the finited States . CO	<u> </u>
	12	
any false, fictitious or frauduled statements or representations as to any matter within its jurisdiction.		

01/29/02 continued

Max press 2650#. 1st RS block 500# - press increase 150#, 2nd block 500# - 100# increase. Flush w/ 36 bbls KCL. ISIP - 1600#, 5 min - 1600#, 10 min - 1500#, 15 min - 1450#. Bleed off press. RD Petroplex. SDFN.

د و المعالم . مراجع مراجع المراجع المراجع المراجع .

> 3-10-25 3-10-25

- 1/30/2002 POH w/ pkr. RIH w/ 2 7/8" & 2 1/16" tbg. POH LD rental strings. RIH w/old 2 3/8" IPC string. SDFN.
- 1/31/2002 POH LD 2 3/8" IPC tbg. Set new 2 7/8" on racks. RIH w/ AD-1 pkr, set pkr @ 4441'. Load backside. SDFN.
- 2/1/2002 Rel pkr & ld 1 jt. Set pkr @ 4409'. Load & test. Csg held. RDSU. Leave well injecting 1200 BPM @ 700#. Final report.