NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional

| instructions in the Rules and Regulati | | Report by Checking Bel | low | |
|--|--|---|---|---------|
| REPORT ON BEGINNING DRILLING OPERATIONS | REPORT ON R OF CASING SH | ESULT OF TEST X | REPORT ON REPAIRING WELL | |
| REPORT ON RESULT OF PLUGGING WELL | REPORT ON RIOPERATION | ECOMPLETION | REPORT FREGING B ACK (Other) | X |
| | Dece | mber 22, 1952 | Hobbs, New Mexico | |
| | (I | Date: | (Place) | |
| Following is a report on the work Markham, Cone an | d Redfern | | Eubenks | |
| · · · · · · · · · · · · · · · · · · · | | Well No. | (Lease) NE SWin the | |
| -21-S -37-E NMPM | Drinkard | Pool, | Lea | County. |
| | | | | |
| | | | cember 19, 1952 | |
| After reaching total dep to 7342 feet with 75 sac 210 joints (6842 feet) o feet with 600 sacks neat | ks neat cement. R f 15.5 lb, J-55, S cement. Plug dow psi for 30 minute | anite, plugged beversed out esti S, new National n 11:30 AM, Dece s. No pressure | ack open hole from 7493 f mated 25 sacks. Then ran casing and cemented at 68 mber 19, 1952. WOC 48 ho loss. Drilled plug from | 552 |
| L. O. Storm | | Cone and Redfer | n Engineer | |
| · (Name |) | (Company) | (1111 e) | |
| Approved: OIL CONSERVATION | COMMISSION | I hereby certify the | 2-4- | - |
| | Kann | Name ZO | Engineer L. O. Sto | |
| (Nam | *) | Position | Markham, Cone and Redfer | מני |
| (Title) | (Date) | Representing | First National Building Lubbock, Texas | |

Address....Lubbock, Texas