## NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

instructions in the Rules and Regulation	Indicate Nature of Report	by Checking Belo	w	
REPORT ON BEGINNING DRILLING OPERATIONS	REPORT ON RESULT		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL	REPORT ON RECOM OPERATION	PLETION	REPORT ON (Other)	
	Novem	ber <b>1</b> 4, 1952	Hobbs, New Me	xico
Following is a report on the work	done and the results obtained un	nder the heading no	ted above at the	
Markham, Cone & Redfern		Eubenk <b>s</b> (Lease)		
Geo. P. Livermore Drill (Contractor	ing Co. , v	Vell No3	• •	Sec <b>14</b> ,
T. 21 S , R. 37 E , NMPM.,	Drinkard	Pool,	Lea	County.
The Dates of this work were as follows:	November 11 & 12. 19	52		•••••
No. 1. In the second of the smooth (suggested in the second of the secon	) (was not) submitted on Form C	-160 on 101 on	November 6	19. <b>52</b>
Notice of intention to do the work (was	) (was not) submitted on Porm C	-1pg 011 <b>1.02</b> 012.	Cross out incorrect words)	, 10
	LED ACCOUNT OF WORK DO			
	Ran 11 joints (237 ag with Texas Pattern Plug down 12:30 A.Mrs. Tested casing with	feet) 13 3/8 shoe and cene	OD, 48 lb., SS, H-40 ented at 249 feet with 1, 1952. Cement	
At total depth 254 feet; new, ST&C National Casir 200 sacks common cement circulated. WOC 24 hour pressure loss. Tests 0.  Witnessed by L. O. Storm (Name)	Ran 11 joints (237 mg with Texas Pattern Plug down 12:30 A.M. rs. Tested casing with K.	feet) 13 3/8 shoe and cene ., November 1 h 500 psi ber	ented at 249 feet with 1, 1952. Cement Fore drilling plug. No  Engineer  (Title)  the information given above is true	•
At total depth 254 feet; new, ST&C National Casir 200 sacks common cement circulated. WOC 24 hour pressure loss. Tests 0.  Witnessed by L. O. Storm (Name)	Ran 11 joints (237 mg with Texas Pattern Plug down 12:30 A.M. rs. Tested casing with K.	shoe and ceme  November 1  Nov	ented at 249 feet with 1, 1952. Cement Fore drilling plug. No  Engineer  (Title)  the information given above is true towards.	e and complete