

NO. OF COPIES RECEIVED	
DISTRIBUTION	
DATE	
NO. OF OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 10-85

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE APPLICATION FOR PERMIT TO DRILL (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

Name of Operator

SHELL OIL COMPANY

Address of Operator

P. O. BOX 991, HOUSTON, TX 77001

Location of Well

UNIT LETTER B 660 FEET FROM THE NORTH LINE AND 1980 FEET FROM
THE EAST LINE, SECTION A14 TOWNSHIP 21 S RANGE 37 E

15. Elevation (Show whether DF, RT, GR, etc.)

3431' DF

7. Unit Agreement Name

8. Name of Lease Holder

SMITH

9. Well No.

2

10. Field and Pool, or Wildcat

DRINKARD, BLINEBRY

11. County

LEA

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

TEMPORARILY ABANDON ☐

DRILL OR ALTER CASING ☐

OTHER ☐

PLUG AND ABANDON ☐

CHANGE PLANS ☐

OTHER ☐

REMEDIAL WORK ☒

COMMENCE DRILLING OPERATIONS ☐

CASING TEST AND CEMENT JOBS ☐

OTHER ☐

ALTERING CASING ☐

PLUG AND ABANDONMENT ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

ACIDIZE DRINKARD ZONE

4-30-80: RU (DA&S) unit. Pld rods & tbg.
5-1-80: Ran (Baker) FB retrievable cementer on 2" tbg & set @6440'. RU acid truck. Acid treated Drinkard openhole 6490-6610' w/2000 gals 15% NE acid in 2 - 1000 gal stages, mixing & ppg 200# benzoic acid & 400# rock salt between stages @Max/Min press 3000/1000 psi. AIR 4 BPM. ISIP 1500 psi. Pld tbg & pkr. Ran (Baker) RBP & pkr on 2" tbg & set RBP @5850'. Set pkr @5675'. Acid treated Blinebry perms 5748-5794' w/2000 gals 15% NE acid in 2 - 1000 gal stages, mixing & ppg 100# benzoic acid & 200# rock salt between stages @Max/Min press 2800/0 psi. AIR 4.3 BPM. ISIP 0. Pld tbg, pkr & RBP. Ran 1 jt 2 1/2" OPMA w/top 3' perf'd, 2" SN + 208 jts 2" EUE 8rd thread tbg 6502' & hung @6509'. OPMA @6480'-6509', SN @6479'. Ran 2" x 1 1/4" x 18' Continental-Emsco pump w/1" x 10' dip tube on 210 - 3/4", 47 - 7/9" rods, 1 - 7/8" x 10' sub on top of string. Started well to ppg.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed A. J. Fore

A. J. FORE

TITLE

SR. ENGR. TECH.

DATE

6/27/80

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: