

NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

X

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

(Place)  
Hobbs, New Mexico

(Date)  
April 27, 1959

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

..... Well No. .... in .....  
 (Company or Operator) ..... Lease ..... F (Unit)  
 Cities Service Oil Co. State S ..... 2  
 (40-acre Subdivision) 1/4 of Sec. ...., R. ...., NMPM, ..... Pool  
 SE NW 15 21S 37E Tubb & Drinkard  
 County.

Lea

FULL DETAILS OF PROPOSED PLAN OF WORK  
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

A Leak has developed in the tubing (Drinkard) of this dual completion well. A 2" bridge plug is now seated in the tubing, separating the two zones.

The 2" bridge plug will be pulled and another plug will be landed in the seating nipple in the Baker Model DB Production Packer. Will load well w/salt water, pull & test tubing. Tubing will be replaced as necessary and down hole seating equipment redressed. The tubing will re-run, tested and spaced out. The locator assembly will be unseated and the water swabbed until the gas zone starts to kick. Seat tbg. locator, flange-up head. Pull bridge plug, swab-in Drinkard, flow Tubbs, take Packer Leakage test & return well to production.

Approved....., 19.....  
Except as follows:

Approved  
OIL CONSERVATION COMMISSION  
By.....  
Title.....

.....  
 Cities Service Oil Co. (Company or Operator)  
 By.....  
 Position.....  
 Send Communications regarding well to:  
 Petroleum Engineer  
 Name.....  
 Address.....  
 G. M. Geyer  
 Box 97, Hobbs, New Mexico