

(Form	1 C-102)
Revised	7/1/52)

NUMBER OF COPIES RECEIVED					
DI	TRIBUTION				
SANTA CI	1				
FILC					
U.S.G. 5					
LAND OFFICE					
TPANSPORTER	01-				
	GAS	1	i		
PHORATION OFFI	C.F.				
OPERATOR					

NEW MEXICO OIL CONSERVATION COMMISSION

HOBBS OFFICE O. C. C. Santa Fe, New Mexico

MISCELLANEOUS NOTICES7 3 37 PH '64

strict Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission

or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

Notice of Intention to Change Plans		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		Notice of Intention to Drill Deeper		
NOTICE OF INTENTION TO PLUG WELL		Notice of Intention to Plug Back	X	Notice of Intention to Set Liner		
NOTICE OF INTENTION TO SQUEEZE TO ACIDIZE			Notice of Intention to Shoot (Nitro)			
Notice of Intention to Gun Perforate	x	Notice of Intention (Other)		Notice of Intention (Other)		

OIL CONSERVATION COMMISSION SANTA FE, NEW MEXICO

Hobbs,	New	Nexice
	(P	lace)

7-27-64 (Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Tidewater				\$	tate	** S **	 Well No.	1	in	D
	(Company or Op					Lease				(Unit)
		15	. T'	215	, R	37B	 	Drinkard		Pcol
(40-acre Subdivision)			,		•					
Lea		County								

.....County.

FULL DETAILS OF PROPOSED PLAN OF WORK (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

We propose to kill well with brine water, plug back inside $5\frac{1}{2}^{w}$ casing with sand or cast iron bridge plug to 6610'. Squeeze off old Brinkard perforations 6560 to 6600'. Run Gamma Ray-Neutron log from retainer at approximately 6540' back to 6000'. Perforate new Drinkard zone with six 3/8" holes at approximately 6505-6530'. Acidize with 1000 gal. 15% NE acid and attempt to ball out. Sand frac with 20,000 gal. refined oil and 1# sand/gal. down 3" tubing. Pull J" frac tubing, and run 2-3/8" tubing and hookwall packer.

Approved	Tidewater Oil Company
Except as follows:	Original Signed By
	By
	Area Supt.
Approved	Send Communications regarding well to:
Approved OIL CONSERVATION COMMISSION	
Ву	Name. C. L. Wade
	Address Box 249, Hobbs, New Mexico
Title	Address