

NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

## MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK	X	NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE	X	NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	X	NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICOHobbs, New Mexico  
(Place)1-19-59  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Cities Service Oil Co. State S Well No. 3 in F  
(Company or Operator) (Unit)

SE 1/4 NW 1/4 of Sec. 15, T. 21S, R. 37E, NMPM, Brunson Pool  
(40-acre Subdivision)

Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK  
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

This well was drilled to 8034' in the Ellenburger. The 5 1/2" casing was set at 8032'. The 5 1/2" casing is perforated as follows: 7975-7990 (60 shots) 7960-7975 (60 shots), 7975-7990 (15 shots), 7990-8000 (40 shots) 7860-7900 (160 shots). The well is SI because it is non-commercial. The following remedial program is proposed to restore this well to commercial status:

Set plug at 7000', dump 10' Calseal on bridge plug. Perforate Abo 6865-6908 (43'), 6913-6920 (7'), 6925-6952 (27') 6955-6965 (10'), (87') 4 jets/ft. (348 shots). Acidize Abo w/1000 reg. acid, test, then acidize w/5000 reg. acid if necessary. If unsuccessful, set plug at 6860 and dump 10' Calseal. Perforate Abo 6790-6803 (13') 6810-6814 (4') 6820-6827 (7') 6840-6847 (7') 4 jets/ft. (124 shots). Acidize Abo w/500 reg. acid, test, then acidize w/2000 gal. reg. acid if necessary. If unsuccessful set plug at 6650' and dump 10' Calseal. Perforate Paddock 5130-5158 (28') 4 jets/ft (112'). Acidize Paddock w/500 gal. reg. acid, test, then acidize w/2000 gal. reg. acid if necessary. If all three are unsuccessful well will be SI and all zones will be re-evaluated prior to plugging.

Approved....., 19.....  
Except as follows:

Cities Service Oil Co.

Company or Operator

By.....

Position..... Dist. Supt.

Send Communications regarding well to:

Approved  
OIL CONSERVATION COMMISSION

By.....

Title.....

Name..... G. M. Geyer

Address..... Box 97, Hobbs, New Mexico