

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	110	110	Sand & caliche
110	1300	1190	Red beds
1300	2820	1520	Anhydrite & salt
2820	7410	4590	Dolomite w/streaks lime, sand, anhydrite & shale
7410	7790	380	Sand & shale w/streaks lime
7790	7920	130	Dolomite & Lime
7920	8061	141	Granite wash
8061	8091	30	Weathered granite
TD	8091		
TOPS BY SCHLUMBERGER:			
Top McKee		7413 (-3984)	
Base McKee		7612 (-4183)	
Top Ellenburger dolomite		7790 (-4361)	
Top Granite Wash		7920 (-4491)	
Top Weathered Granite		8061 (-4632)	
DST #1:	7378-7610 (McKee Sand)		5/8" BC & 1" TC on 3 1/2" DS. Tool open 150 min. Gas to surface in 9 min. Fluid in 26 min. Oil in 45 min. Flowed 54.51 bbls. oil in 90 min. Stable rate of flow at end of test 25 bbls./hour. GOR 1377. FBHP 1200 p.s.i. 15 min. SIBHP 2200 p.s.i. Hydrostatic mud head 3900 p.s.i. <u>Positive Test.</u>
DST #2:	7921-8091 (Granite Wash)		Tool open 60 min. Fair air blow throughout test. Recovered 135' (1 bbl.) drlg. fluid w/no shows. FBHP 0 p.s.i. 15 min. SIBHP 0 p.s.i. HMH 4300 p.s.i. <u>Positive Test.</u>