SANTA FE C-NHOCK 1-Mr. E. H. Shuler - Houston 1-Mr. E. M. Indeme Type of Lone 1-Mr. E. Pierce - Midland			IVED	-:							
THE I - Rr. E. H. Shular - Houston 1-Mr. J. E. Pierce - Midland	SANTA F		N			MEXICO OIL CONS	ERVATION COMM	MISSION		Form C-101 Revised 1-1-6	5
The Abo Zone is presently NIO. It is proposed to plug off the Abo and test the San Andres Zone as follows: 1. Run Games Ray-Sonic Log with Collar locator from 5000-3000'. 2. Set CIP # 4500', w/35' casent on top. 3. Perforts San Andres Zone as follows: 1. Run Games Ray-Sonic Log with Collar locator from 5000-3000'. 2. Set CIP # 4500', w/35' casent on top. 3. Perforts San Andres Zone as follows: 1. Run Games Ray-Sonic Log with Collar locator from 5000-3000'. 2. Set CIP # 4500', w/35' casent on top. 3. Perforts San Andres Zone and Advance San Andres Zone as follows: 1. Run Games Ray-Sonic Log with Collar locator from 5000-3000'. 3. Perforts San Andres Zone and Andres Zone as follows: 1. Run Games Ray-Sonic Log with Collar locator from 5000-3000'. 3. Perforts San Andres Zone and Andres Zone as follows: 1. Run Games Ray-Sonic Log with Collar locator from 5000-3000'. 3. Perforts San Andres Zone and Andres Zone as follows: 1. Run Games Ray-Sonic Log with Collar locator from 5000-3000'. 4. Treat perforations w/2,000 gals. 15 be 30 caid, using ball sealers. Prac w/20,000 gals. 99 gelled brine and 30,000\$ 20-40 sand. 5. Swab test. MAR 9 1972. SIDEPLUISOR DISTRICT! MAR 9 1972.		E				u Chular -	Manatan				
APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK Top of Note DEEPEN PLUG BACK TOTAL STATE 187 PLUG BACK TOTAL STATE 187 PLUG BACK TOTAL STATE 187 STATE											¬ ' —
APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK THE OF BUILD DEEPEN PLUG BACK THE OF BUILD THE OF BUILD DEEPEN PLUG BACK THE OF BUILD THE OF BUILD THE OF BUILD DEEPEN PLUG BACK THE OF BUILD THE ABO ZONE IS PRESENTLY NIO. It is proposed to plug off the Abo and test the San Andreas Zone as follows: 1. Run Gamma Ray-Sonic Log with Collar locator from 5000-3000'. 2. Set CIPP 4 500', w/35' cament on top. 3. Perforate Ban Andreas (To be picked from Log). 4. Treat perforations w/2,000 gais. 15 be 30 acid, using ball sealers. Frac w/20,000 gais. 94 gelled brine and 30,000\$ 20-40 sand. THE ABOYS EMPLY DESIRIES FROM SET OF BUILD				-++		E. Pierce -	wigiand				
APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK 4. Type of Wolf 5. Type of Wolf 6. Type of Wolf 7. Proposition 6. Deepen Plug Back 6. Proposition				- 4	-LTTG						
DEPPEN DE PEND DE PEND DEPPEN DE PEND DE P		JR 								minn.	innimini
DEPPEN DE PEND DE PEND DEPPEN DE PEND DE P		A D.	OL LOATIO	V EOD DE	DALE TO I	DDÚL DEEDEN	OP PLUG BAC	~K			
DEPEND DRILL DEEPEND DRILL DRILL DRIL	T		LICATIO	N FOR PE	RMIT TO	DRILL, DEEPEN	, OR PLUG BAC	<u> </u>		7. Unit Agree	ement Name
The Abo Zone is presently NIO. It is proposed to plug off the Abo and test the San Andreas Zone as follows: 1. Run Gamma Ray-Sonic Log with Collar locator from 5000-3000'. 2. Set CIEB © 4500', w/35' cement on top. 3. Perforate Sono w/2,000 gals. 15t DB-30 acid, using ball sealers. Prac w/20,000 gals. 98 gelled brine and 30,000\$ 20-40 sand. NAGOVE SPACE DESCRIBE ORGOSED PROGRAM IF PROPOSED, IS TO SEEPEN OF PLUS BACK, EVE DATA OR PRESENT PRODUCTIVE FORE AND PROPOSED AND RESERVED PROPOSED STANDARD PROPOSED PROPOSED STANDARD PROPOSED PROPOSED STANDARD PROPOSED PRO	ra, Type or	WORK								-	
The Abo Zone is presently NIO. It is proposed to plug off the Abo and test the San Andres Zone as follows: 1. Run Gasma Ray-Sonic Log with Collar locator from 5000-3000'. 2. Set CIDP @ 4500', w/35' cement on top. 3. Perforations w/2,000 gals. 159 gelled brine and 30,000\$ 20-40 sand. NAMES SAN ANDRES 1. Run Gasma Ray-Sonic Log with Collar locator from 5000-3000'. 2. Set CIDP @ 4500', w/35' cement on top. 3. Perforations w/2,000 gals. 159 DB-30 acid, using ball sealers. Frac w/20,000 gals. 99 gelled brine and 30,000\$ 20-40 sand. NAMES SAN ANDRES 1. Run Gasma Ray-Sonic Log with Collar locator from 5000-3000'. 3. Set CIDP @ 4500', w/35' cement on top. 3. Perforations w/2,000 gals. 159 DB-30 acid, using ball sealers. Frac w/20,000 gals. 99 gelled brine and 30,000\$ 20-40 sand. NAMES SAN ANDRES 1. Run Gasma Ray-Sonic Log with Collar locator from 5000-3000'. 3. Set CIDP @ 4500', w/35' cement on top. 4. Treat perforations w/2,000 gals. 159 DB-30 acid, using ball sealers. Frac w/20,000 gals. 99 gelled brine and 30,000\$ 20-40 sand. 5. Swab test. NAMES 3 1977. SIMPROVE SANCE DESCRIPE SURPRISED FROM SURPRISED FROM SURPRISED FROM SURPRISED FRACE SURPRISED FRAC	1. Total of	Well	DRILL 💹			DEEPEN		PLUG B	ACK	8. Farm or L	ease Name
The Abo Zone is presently NIO. It is proposed to plug off the Abo and test the San Andres Zone as follows: 1. Run Gamma Ray-Sonic Log with Collar locator from 5000-3000'. 2. Set CIBP 0 4500', w/35' cament on top. 3. Perforate San Andres (To be picked from Log). 3. Perforate San Andres (To be picked from Log). 4. Treat perforations w/2,000 gals. 9e gelled brine and 30,000# 20-40 sand. N. ADDUS SPRACE ESCRIPS CROPPED REPORTED REPORTED REPORT OF PROPOSED LIST DEPTH AND REPORTED REPORTED REPORTED REPORTS OF COMMENT. Practice of the Report o			GAS								
The Abo Zone is presently NIO. It is proposed to plug off the Abo and test the San Andres Zone as follows: 1. Run Gamas Ray-Sonic Log with Collar locator from 5000-3000'. 2. Set CIBP @ 4500', w/35' cement on top. 3. Perforate San Andres (To be picked from Log). 3. Perforation w/2,000 gals. 159 gelled brine and 30,000\$ 20-40 sand. A BOVE SANCE DESCRIBE SHOPPED PROCESMENT FRO CAME IN THE ARRA ENGINEER. A BOVE SANCE DESCRIBE SHOPPED PROCESMENT FRO CAME IN THE ARRA ENGINEER. A BOVE SANCE DESCRIBE SHOPPED PROCESMENT FRO CAME IN THE ARRA ENGINEER. A BOVE SANCE DESCRIBE SHOPPED PROCESMENT FRO CAME IN THE ARRA ENGINEER. A BOVE SANCE DESCRIBE SHOPPED PROCESMENT FRO CAME IN THE ARRA ENGINEER. A BOVE SANCE DESCRIBE SHOPPED PROCESMENT FRO CAME IN THE ARRA ENGINEER. The ABOVE SANCE DESCRIBE SHOPPED PROCESMENT FRO CAME IN THE ARRA ENGINEER. A BOVE SANCE DESCRIBE SHOPPED PROCESMENT FRO CAME IN THE ARRA ENGINEER. The ARRA ENGINEER. The ARRA ENGINEER. Berely cently that the information shows is true and compiles to the heat of my knowledge and better. SINDEPLUSOR DISTRICT I MARK 3 1972.			WELL	стн	R		ZONE		ZONE L		S"
The Abo Zone is presently NIO. It is proposed to plug off the Abo and test the San Andres Zone as follows: 1. Run Gamma Ray-Sonic Log with Collar locator from 5000-3000'. 2. Set CISP 6 4500', w/35' cament on top. 3. Perforate San Andres (To be picked from Log). 3. Perforate San Andres (To be picked from Log). 4. Treat perforations w/2,000 gals. 15th 0-30 acid, using ball scalers. Frac w/20,000 gals. 9th gelled brine and 30,000\$th 20-40 sand. 5. Swab test. 1. Randows space describe enonoged Program is represented by the sand and set the San Andres (To be picked from Log). 5. Swab test. 1. Randows space describe enonoged Program is represented by the sand and set the San Andres (To be picked from Log). 5. Swab test. 1. Randows space describe enonoged Program is represented by the sand and set the San Andres (To be picked from Log). 5. Swab test. 1. Randows space describe enonoged Program is represented by the sand. 5. Swab test. 1. Randows space describe enonoged Program is represented to the best of my knowledge and boilet. 1. Randows space describe enonoged is thus above is true and complete to the best of my knowledge and boilet. 1. Randows space describe the sand sover is true and complete to the best of my knowledge and boilet. 1. Randows space describe the sand complete to the best of my knowledge and boilet. 1. Randows space describe the sand sover is true and complete to the best of my knowledge and boilet. 1. Randows space describe the sand complete to the best of my knowledge and boilet. 1. Randows space describe the sand complete to the best of my knowledge and boilet. 1. Randows space describe the sand complete to the best of my knowledge and boilet. 1. Randows space describe the sand complete to the best of my knowledge and boilet.										5,	
The Abo Zone is presently NIO. It is proposed to plug off the Abo and test the San Andres Zone as follows: 1. Run Gasma Ray-Sonic Log with Collar locator from 5000-3000'. 2. Set CIBP @ 4500', w/35' cessent on top. 3. Perforate San Andres (To be picked from Log). 4. Treat perforations w/2,000 gals. 154 No. 156 No. 200-40 sand. 5. Swab test. PARE DESCRIPTION OF THE PROPOSED PROGRAM: IF PROPOSED IS 156 No. 300-3000' and 200-40 sand. The Above space describe PROPOSED PROGRAM: If PROPOSED Is 156 No. 300-3000' and 200-3000' and										10 Field do	d Pool or Wildort
The Abo Zone is presently NIO. It is proposed to plug off the Abo and test the San Andres Zone as follows: 1. Run Gamma Ray-Sonic Log with Collar locator from 5000-3000'. 2. Set CIBP @ 4500', w/35' cement on top. 3. Perforate San Andres (To be picked from Log). 4. Treat perforations w/2,000 gals. 15% nest 2000 gals. 15% nes	3. Address o	of Operat	ot							10. Tield dis	1 Foot, or wilded
The Abo Zone is presently NIO. It is proposed to plug off the Abo and test the San Andres Zone as follows: 1. Run Gamma Ray-Sonic Log with Collar locator from 5000-3000'. 2. Set CIBP 6 4500', w/35' cement on top. 3. Perforate San Andres (To be picked from Log). 4. Treat perforations w/2,000 gals. 15% DB-30 acid, using ball sealers. Frac w/20,000 gals. 9% galled brine and 30,000% 20-40 sand. N. ABOVE SPACE DESCRIBE ENOPOSED DROGRAM IF PROPOSEL IS TO SEPPEN ON PLUS BACK, GIVE DATA ON ERCERNI PRODUCTIVE IONE AND PROPOSED NEW PROPOSED										WANTER A	mmm
The Abo Zone is presently NIO. It is proposed to plug off the Abo and test the San Andres Zone as follows: 1. Run Gamma Ray-Sonic Log with Collar locator from 5000-3000'. 2. Set CIBP @ 4500', w/35' cement on top. 3. Perforate San Andres (To be picked from Log). 4. Treat perforations w/2,000 gals. 15% DS-30 acid, using ball sealers. Frac w/20,000 gals. 9% gelled brine and 30,000% 20-40 sand. N. ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSED IS TO BEEPEN OF PLUG BACK, GIVE DATA DO PROSED NEW AND PROPOSED NE	4. Location	of Well	UNIT LETTE	R D	LOCA	ATED <u>660</u>	FEET FROM THE	NORTH	LINE		
The Abo Zone is presently NIO. It is proposed to plug off the Abo and test the San Andres Zone as follows: 1. Run Gamma Ray-Sonic Log with Collar locator from 5000-3000'. 2. Set CIBP @ 4500', w/35' cement on top. 3. Perforate San Andres (To be picked from Log). 4. Treat perforations w/2,000 gals. 15% DS-30 acid, using ball sealers. Frac w/20,000 gals. 9% gelled brine and 30,000% 20-40 sand. N. ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSED IS TO BEEPEN OF PLUG BACK, GIVE DATA DO PROSED NEW AND PROPOSED NE											
The Abo Zone is presently NIO. It is proposed to plug off the Abo and test the San Andres Zone as follows: 1. Run Gamma Ray-Sonic Log with Collar locator from 5000-3000'. 2. Set CIBP @ 4500', w/35' cement on top. 3. Perforate San Andres (To be picked from Log). 4. Treat perforations w/2,000 gals. 15t DB-30 acid, using ball sealers. Frac w/20,000 gals. 9t gelled brine and 30,000\$ 20-40 sand. 5. Swab test. NABOVE SPACE DESCRIBE PROPOSED PROGRAM: If PROPOSEL IS TO DEEPEN ON PLUS SACK, GIVE DATA ON PROSECTIVE ZONE AND PROPOSED NEW	AND 9	90	FEET FROM	THE WE	T LINE	E OF SEC. 15	TWP. 21-5 RG	SE 37-1	NMPM	13 County	<i></i>
The Abo Zone is presently NIO. It is proposed to plug off the Abo and test the San Andres Zone as follows: 1. Run Gamma Ray-Sonic Log with Collar locator from 5000-3000'. 2. Set CIBP @ 4500', w/35' cement on top. 3. Perforate San Andres (to be picked from Log). 4. Treat perforations w/2,000 gals. 15t DB-30 acid, using ball sealers. Frac w/20,000 gals. 9t gelled brine and 30,000\$ 20-40 sand. N. ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If PROPOSAL IS TO SEEPEN OR PLUS BACK, SIVE DATA OR PROSENT PRODUCTIVE ZONE AND PROPOSED NEW PROPOSE											
SAN ANDRES 3448' G.R. PROPOSED CASING AND CEMENT PROGRAM SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SIZE OF CASING WEIGHT PER FOOT SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP The Abo Zone is presently NIO. It is proposed to plug off the Abo and test the San Andress Zone as follows: 1. Run Gamma Ray-Sonic Log with Collar locator from 5000-3000'. 2. Set CIBP @ 4500', w/35' cement on top. 3. Perforate San Andress (To be picked from Log). 4. Treat perforations w/2,000 gals. 15% DS-30 acid, using ball sealers. Frac w/20,000 gals. 9% gelled brine and 30,000% 20-40 sand. 5. Swab test. N. ABONE SPACE DESCRIPE PROPOSED DEOGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PROPOSED NEW PROPOSED STATE OF THE PROPOSED NEW PROPOSED WINDOW PROPOSED OF THE PROPOSED NEW PROPOSED NEW PROPOSED STATE OF THE PROPOSED NEW PROPOSED STATE OF THE PROPOSED NEW PROPOSED NEW PROPOSED NEW PROPOSED STATE OF THE PROPOSED NEW PR					7/////		77777777	77777	77777	LEA	HHHH
SAN ANDRES 3448' G.R. PROPOSED CASING AND CEMENT PROGRAM SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP The Abo Zone is presently NIO. It is proposed to plug off the Abo and test the San Andres Zone as follows: 1. Run Gamma Ray-Sonic Log with Collar locator from 5000-3000'. 2. Set CIBP @ 4500', w/35' cement on top. 3. Perforate San Andres (To be picked from Log). 4. Treat perforations w/2,000 gals. 15% DS-30 acid, using ball sealers. Frac w/20,000 gals. 9% gelled brine and 30,000% 20-40 sand. 5. Swab test. NABONE SPACE DESCRIBE PROPOSED DROGRAM: IF PROPOSAL IS TO DEEPEN ON PLUG BACK, SIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PROPOSED NEW PROPOSED HOW PROVIDED IN THE AREA ENGINEER WARRAND TITLE AREA ENGINEER Date 3-8-72 WARR 9 1972.	[[]]	IIII									
SAN ANDRES 3448' G.R. PROPOSED CASING AND CEMENT PROGRAM SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SIZE OF CASING WEIGHT PER FOOT SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP The Abo Zone is presently NIO. It is proposed to plug off the Abo and test the San Andress Zone as follows: 1. Run Gamma Ray-Sonic Log with Collar locator from 5000-3000'. 2. Set CIBP @ 4500', w/35' cement on top. 3. Perforate San Andress (To be picked from Log). 4. Treat perforations w/2,000 gals. 15% DS-30 acid, using ball sealers. Frac w/20,000 gals. 9% gelled brine and 30,000% 20-40 sand. 5. Swab test. N. ABONE SPACE DESCRIPE PROPOSED DEOGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PROPOSED NEW PROPOSED STATE OF THE PROPOSED NEW PROPOSED WINDOW PROPOSED OF THE PROPOSED NEW PROPOSED NEW PROPOSED STATE OF THE PROPOSED NEW PROPOSED STATE OF THE PROPOSED NEW PROPOSED NEW PROPOSED NEW PROPOSED STATE OF THE PROPOSED NEW PR								71177	77777		
21A. Kimo 6 Storus Plug. Bond 21B. Drilling Centractor 3448' G.R. PROPOSED CASING AND CEMENT PROGRAM SIZE OF HOLE SIZE OF CASING SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP The Abo Zone is presently NIO. It is proposed to plug off the Abo and test the San Andres Zone as follows: 1. Run Gamma Ray-Sonic Log with Collar locator from 5000-3000'. 2. Set CIBP @ 4500', w/35' cament on top. 3. Perforate San Andres (To be picked from Log). 4. Treat perforations w/2,000 gals. 15% DE-30 acid, using ball sealers. Frac w/20,000 gals. 9% gelled brine and 30,000% 20-40 sand. 5. Swab test. NABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUS BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PROPOSED NEW PROPOSED STATE OF THE BROKEN, IF ANY. Thereby certify that the information above is true and complete to the best of my knowledge and belief. SETUDEPTIES OR DISTRICT F. DATA DATA SHOW THE PROPOSED NEW PROP	11111	1111		IIIIII			19. Proposed Dept	th 19	A. Formatio	on .	20. Hotary or C.T.
PROPOSED CASING AND CEMENT PROGRAM SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP The Abo Zone is presently NIO. It is proposed to plug off the Abo and test the San Andres Zone as follows: 1. Run Gamma Ray-Sonic Log with Collar locator from 5000-3000'. 2. Set CIBP @ 4500', w/35' cement on top. 3. Perforate San Andres (To be picked from Log). 4. Treat perforations w/2,000 gals. 15% DS-30 acid, using ball sealers. Frac w/20,000 gals. 9% gelled brine and 30,000% 20-40 sand. 5. Swab test. N. ABONE SPACE DESCRIBE PROPOSED PROGRAMM IF PROPOSAL IS TO BEEPEN ON PLUE BACK, SIVE DATA ON PRESENT PRODUCTIVE IONE AND PROPOSED NEW PROPOSED NEW PROPOSED STATE CHARLES AND PROPOSED NEW PROPOSED STATE CHARLES AND PROPOSED NEW PROPOSED N							1		SAN AND		
PROPOSED CASING AND CEMENT PROGRAM SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP The Abo Zone is presently NIO. It is proposed to plug off the Abo and test the San Andres Zone as follows: 1. Run Gamma Ray-Sonic Log with Collar locator from 5000-3000'. 2. Set CIBP @ 4500', w/35' cement on top. 3. Perforate San Andres (To be picked from Log). 4. Treat perforations w/2,000 gals. 15t DS-30 acid, using ball sealers. Frac w/20,000 gals. 9t gelled brine and 30,000# 20-40 sand. 5. Swab test. NABOVE SPACE DESCRIBE PROPOSED PROGRAM: If PROPOSAL IS TO DEEPEN OR PLUS BACK, GIVE DATA ON PRESENT PRODUCTIVE IONE AND PROPOSED NEW PROPOSED NEW PROPOSED NEW PROPOSED IN STRUCT I THE AREA ENGINEER Title AREA ENGINEER Date 3-8-72 (This pace for Stage Use) MAR 9 1972.	21. Elevatio	ons (Show	whether DF,	RT, etc.)	21A. Kind	& Status Plug. Bond	21B. Drilling Cont	tractor		22. Approx	. Date Work will start
SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP The Abo Zone is presently NIO. It is proposed to plug off the Abo and test the San Andres Zone as follows: 1. Run Gamma Ray-Sonic Log with Collar locator from 5000-3000'. 2. Set CIBP @ 4500', w/35' cement on top. 3. Perforate San Andres (To be picked from Log). 4. Treat perforations w/2,000 gals. 15% DS-30 acid, using ball sealers. Frac w/20,000 gals. 9% gelled brine and 30,000% 20-40 sand. 5. Swab test. NABBUYE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUE BACK, GIVE DATA ON PRESENT PRODUCTIVE IONE AND PROPOSED NEW PROPOSED NEW PROPOSED WITH PROPOSED NEW PROPOSED NEW PROPOSED WITH PROPOSED BY THE AREA ENGINEER Title AREA ENGINEER MAR 9 1972		34481	G.R.				PULLING	UNIT			
The Abo Zone is presently NIO. It is proposed to plug off the Abo and test the San Andres Zone as follows: 1. Run Gamma Ray-Sonic Log with Collar locator from 5000-3000'. 2. Set CIBP @ 4500', w/35' cement on top. 3. Perforate San Andres (To be picked from Log). 4. Treat perforations w/2,000 gals. 15t D8-30 acid, using ball sealers. Frac w/20,000 gals. 9% gelled brine and 30,000% 20-40 sand. 5. Swab test. NABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUS BACK, GIVE DATA ON PROSECTIVE IONE AND PROPOSED NEW PRODUCTIVE IONE AND PROPOSED NEW PRODuctive to the best of my knowledge and belief. Date	23.					DODOSED CASINO A	ND CENENT DOCC	·D 4 4			
The Abo Zone is presently NIO. It is proposed to plug off the Abo and test the San Andres Zone as follows: 1. Run Gamma Ray-Sonic Log with Collar locator from 5000-3000'. 2. Set CIBP @ 4500', w/35' cement on top. 3. Perforate San Andres (To be picked from Log). 4. Treat perforations w/2,000 gals. 15% DS-30 acid, using ball sealers. Frac w/20,000 gals. 9% gelled brine and 30,000% 20-40 sand. 5. Swab test. NABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW					P	ROPUSED CASING A	.ND CEMENT PROG	KAM			
1. Rum Gamma Ray-Sonic Log with Collar locator from 5000-3000'. 2. Set CIBP @ 4500', w/35' cement on top. 3. Perforate San Andres (To be picked from Log). 4. Treat perforations w/2,000 gals. 15% DS-30 acid, using ball sealers. Frac w/20,000 gals. 9% gelled brine and 30,000% 20-40 sand. 5. Swab test. N. ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRODUCTIVE ZONE, GIVE BLOWGUT PREVENTER PROGRAM, IF ANY. Thereby certify that the information above is true and complete to the best of my knowledge and belief. PRINCIPLE STATE OF THE USE. Title AREA ENGINEER Date 3-8-72 MAR 9 1972	SIZE	E OF H	OLE	SIZE OF	CASING	WEIGHT PER FO	OT SETTING D	EPTH	SACKS O	F CEMENT	EST. TOP
1. Rum Gamma Ray-Sonic Log with Collar locator from 5000-3000'. 2. Set CIBP @ 4500', w/35' cement on top. 3. Perforate San Andres (To be picked from Log). 4. Treat perforations w/2,000 gals. 15% DS-30 acid, using ball sealers. Frac w/20,000 gals. 9% gelled brine and 30,000% 20-40 sand. 5. Swab test. N. ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRODUCTIVE ZONE, GIVE BLOWGUT PREVENTER PROGRAM, IF ANY. Thereby certify that the information above is true and complete to the best of my knowledge and belief. PRINCIPLE STATE OF THE USE. Title AREA ENGINEER Date 3-8-72 MAR 9 1972											
1. Rum Gamma Ray-Sonic Log with Collar locator from 5000-3000'. 2. Set CIBP @ 4500', w/35' cement on top. 3. Perforate San Andres (To be picked from Log). 4. Treat perforations w/2,000 gals. 15% DS-30 acid, using ball sealers. Frac w/20,000 gals. 9% gelled brine and 30,000% 20-40 sand. 5. Swab test. N. ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRODUCTIVE ZONE, GIVE BLOWGUT PREVENTER PROGRAM, IF ANY. Thereby certify that the information above is true and complete to the best of my knowledge and belief. PRINCIPLE STATE OF THE USE. Title AREA ENGINEER Date 3-8-72 MAR 9 1972											
1. Rum Gamma Ray-Sonic Log with Collar locator from 5000-3000'. 2. Set CIBP @ 4500', w/35' cement on top. 3. Perforate San Andres (To be picked from Log). 4. Treat perforations w/2,000 gals. 15% DS-30 acid, using ball sealers. Frac w/20,000 gals. 9% gelled brine and 30,000% 20-40 sand. 5. Swab test. N. ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRODUCTIVE ZONE, GIVE BLOWOUT PREVENTER PROGRAM, IF ANY. hereby certify that the information above is true and complete to the best of my knowledge and belief. Dispinal Signed Title AREA ENGINEER Date 3-8-72 (This space for State Use) MAR 9 1972											
1. Rum Gamma Ray-Sonic Log with Collar locator from 5000-3000'. 2. Set CIBP @ 4500', w/35' cement on top. 3. Perforate San Andres (To be picked from Log). 4. Treat perforations w/2,000 gals. 15% DS-30 acid, using ball sealers. Frac w/20,000 gals. 9% gelled brine and 30,000% 20-40 sand. 5. Swab test. N. ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRODUCTIVE ZONE, GIVE BLOWGUT PREVENTER PROGRAM, IF ANY. Thereby certify that the information above is true and complete to the best of my knowledge and belief. PRINCIPLE STATE OF THE USE. Title AREA ENGINEER Date 3-8-72 MAR 9 1972						1			J		
hereby certify that the information above is true and complete to the best of my knowledge and belief. Distribut State By the process of the process of the best of my knowledge and belief. Signed	1.	Run Set Per:	Gamma I CIBP @ forate S	Ray-Sonio 4500', w	//35 ce s (To b	ment on top.		000-30	0001.		
SUPERVISOR DISTRICT 1 MAR 9 1972	4.	w/2	0,000 ga				8-30 acid, u		oall se	alers. E	rec.
SUPERVISOR DISTRICT 1 MAR 9 1972	A. 5. N ABOVE STIVE ZONE. Chereby cert	SPACE D	ESCRIBE PI	ROPOSED PR TER PROGRAM, ion above is t	ogram: IF	PROPOSAL IS TO DEEPE	S-30 acid, us 000 20-40 so on or plug back, give y knowledge and bel	and.		RODUCTIVE ZONI	
SUPPLIES TO THE PROPERTY OF THE PARTY OF THE	4. 5.	SPACE D	ESCRIBE PERSON THE PREVENT PREVENT PREVENT PREVENT THE INFORMATION TO THE INFORMATION THE INFORMATION TO THE	ROPOSED PROFER PROGRAM,	ogram: IF	PROPOSAL IS TO DEEPE	S-30 acid, us 000 20-40 so on or plug back, give y knowledge and bel	and.		RODUCTIVE ZONI	
	A. 5. N ABOVE STIVE ZONE. Control hereby cert	SPACE D	ESCRIBE PERSON THE PREVENT PREVENT PREVENT PREVENT THE INFORMATION TO THE INFORMATION THE INFORMATION TO THE	ROPOSED PROFER PROGRAM,	ogram: IF	PROPOSAL IS TO DEEPE plete to the best of m	S-30 acid, wo	e DATA ON	I PRESENT P	Date3_	E AND PROPOSED NEW PROD

A Company

MARK STORY

OIL CONSERVATION COMMA. HORES, N. W.

Form C-102 Supersedes C-128 Effective 1-1-65

perator			All dista	nces must be from	ease	underies of	the Section		We	ll No.
GETTY C	IL C	OMPANY			STATE "S"					5
nit Letter D	Sectio	n 15	Township	21-9	Range	37-E	County	Lea		
ctual Footage Loc	ation of						<u> </u>			
660		from the	RTH	line and	990	feet	t from the	WEST	line	
round Level Elev. 3448		Producing For SAN A		P.	nol I	UMICR			Dedicated	Acres 40 Acres
		ogo dadina	ted to the	subject well			r hachure	marks on t	he plat he	
interest as	nd roya an one	alty). Lease of d	ifferent ov	vnership is de	dicated to			_		oth as to working
If answer this form i	is "noif nece	No If a b," list the ssary.)	owners an	vell until all in	consolidations whice	h have ac	tually be	ted (by con	mmunitizat	e reverse side of ion, unitization, I by the Commis-
					i				CERTIF	CATION
NO.	5	 						Name E. J. Position AREA E Company GSTT	erein is true my knowledg MIGINAL 21.00 MIGINE 1.00 MILLER MILLER	the information con- and complete to the e and belief.
								I hereby shown o nates of under my is true knowled	y certify the nothing this plat was factual survey supervisions and correcting and belie	
0 330 660	190 1	320 1650 19	80 2310 26	540 2000	1500	1000	411.11	and/or La	nd Surveyor	

RECEIVED

MAR (1972 OIL CONSERVATION COMM. HOBBS, N. M.