

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER) X- Dual Complete	

OIL CONSERVATION COMMISSION
 SANTA FE, NEW MEXICO

Eunice, New Mexico
 (Place)

February 7, 1962
 (Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Amerada Petroleum Corporation - State D"A" Well No. **2** in **BK**
 (Company or Operator) (Unit)
NW 1/4 of Sec. **16**, T. **21-S**, R. **36-E**, NMPM., **Drinkard** Pool
 (40-acre Subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
 (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

6651' DOD - Pull tubing and packer, run 3½" tubing w/packer & holddown & sand oil frac Drinkard perforations from 6555' to 6648' w/20,000 gallons crude oil & 20,000# sand w/1/20th Lb. Adomite per gallon and swab test. Pull 3½" tubing, packer and holddown and run Baker Model "D" Packer and set at approximately 6450'. Perforate Blinebry zone from 5803'-5807', 5840'-5844', 5854'-5858', 5872'-5877', 5885'-5895', 5920'-5924' and 5928' to 5932' w/2 shots per foot, Run 3½" tubing and set a retrievable bridge plug ~~xxx~~ at approximately 6000' w/sand dumped on top. Acidize Blinebry perforations w/1,500 gallons of 15% Regular acid using 105 ball sealers and swab test. Then sand oil fracture these above perforations w/30,000 gallons crude oil and 30,000# of 20/40 sand using Adomite and 105 ball sealers and swab test. Pull 3½" tubing and retrieve bridge plug, run dual strings of 2-1/16" OD tubing (with sliding sleeve assembly in Drinkard string) and complete as an oil-oil dual.

Approved....., 19.....
 Except as follows:

Approved
 OIL CONSERVATION COMMISSION

By.....
 Title.....

Amerada Petroleum Corporation
 Company or Operator

By.....
 Position **Asst. Dist. Supt.**

Send Communications regarding well to:

Amerada Petroleum Corporation
 Name.....
Box 706, Eunice, New Mexico
 Address.....