

Place Monument, New Mexico  
Date June 30, 1947

|   |   |   |   |
|---|---|---|---|
|   |   |   |   |
|   |   |   |   |
| D | C | B | A |
| E | F | G | H |
| L | K | J | I |
| M | N | O | P |

Glenn Staley  
Proration Office  
Hobbs, New Mexico

Designate UNIT well is located in  
"X"

NOTION OF COMPLETION OF: (Lease) State DA Well No. 2 ~~1000~~  
1980 feet from South line: 1980 feet from West line;  
Section 16 Township 21S Range 37E

DATE STARTED May 14, 1947  
DATE COMPLETED June 25, 1947  
ELEVATION 3465' Derrick Floor, 3454' Ground  
TOTAL DEPTH S.L. 6654' Drilled out depth 6651'  
CABLE TOOLS \_\_\_\_\_ ROTARY TOOLS X

#### CASING RECORD

|      |                |       |             |            |             |
|------|----------------|-------|-------------|------------|-------------|
| SIZE | <u>13 3/8"</u> | DEPTH | <u>214</u>  | SAX CEMENT | <u>200</u>  |
| SIZE | <u>8 5/8"</u>  | DEPTH | <u>2815</u> | SAX CEMENT | <u>1250</u> |
| SIZE | <u>5 1/2"</u>  | DEPTH | <u>6654</u> | SAX CEMENT | <u>500</u>  |

#### TUBING RECORD

SIZE 2" EUE DEPTH 6645' Open ended

#### ACID RECORD

NO. GALS. 250 Mud Acid Western  
NO. GALS. 1000 Dowell  
NO. GALS. \_\_\_\_\_

#### SHOT RECORD

NO. CTS. \_\_\_\_\_  
NO. CTS. \_\_\_\_\_  
NO. CTS. \_\_\_\_\_

#### FORMATION TOPS

|                   |                       |                                 |                 |              |
|-------------------|-----------------------|---------------------------------|-----------------|--------------|
|                   | Anhydrite             | <u>1230'</u>                    | Base San Andres | <u>5150'</u> |
|                   | Top Salt              | <u>1330'</u>                    | Top Clear Fork  | <u>5620'</u> |
|                   | Base Salt             | <u>2470'</u>                    | Top of Tubbs    | <u>6110'</u> |
| Zone 1 Yates      | <del>Red Sand</del>   | <u>2660'</u>                    |                 |              |
| Top Eunice Line   | <del>Brownish</del>   | <u>2730'</u>                    |                 |              |
| Top Monument Line | <del>White Line</del> | <u>2770'</u>                    |                 |              |
|                   | Oil or Gas Pay        | <u>6600-6648 - Perforations</u> |                 |              |
|                   | Water                 | _____                           |                 |              |

Initial Production Test ~~SAFETY CHECKS~~ Pumping \_\_\_\_\_ Flowing ~~EXCESSIVE KICKS~~  
Test After Acid or Shot Flowed 96.87 bbls oil in 13 hours 1/2" Positive choke, Gas Volume  
Initial GAS VOLUME 119,700 Gas Oil Ratio 736, Gravity of oil 35.8 corrected

SCHEDULE NO. \_\_\_\_\_ DATE June 30, 1947

PIPE LINE TAPPING OIL Magnolia Pipe Line Company

REMARKS: Perforated 6623 to 6648-100 shots COMPANY: Amerada Petroleum Corporation  
would not flow, perforated 6600-6623' and  
well started flowing, and acidized with SIGNED BY: Don Toppo  
1000 Gals of Dowell XXFL-15% Acid with  
Dowell Pilot Survey.

