


OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS



Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	X	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

August 7, 1947

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____
Amerada Petroleum Corporation State **DA** Well No. **3** in the _____

Company or Operator _____ Lease _____
NW 1/4 SE 1/4 of Sec. **16**, T. **21S**, R. **37E**, N. M. P. M.,
Drinkard Field, **Lea** County.

The dates of this work were as follows:

August 6, 7, 1947

Notice of intention to do the work was (~~submitted~~) submitted on Form C-102 on **August 4,** 19 **47**
 and approval of the proposed plan was (~~submitted~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

6630' Total Depth Line. Ran temperature survey and found top of cement at 2845', 96% of calculated fill. Nipple up, went in hole with tubing and found top of cement at 6547'. Tested casing with 1000# for 30 minutes and was OK. Drilled out cement to 6629' and tested casing with 1000# for 30 minutes and was OK. Gun perforated with Lane-Wells from 6524' to 6629', 420 shots. Ran 211 joints of 2" EUE 4.7#, J-55, R-2, 8-BT Spang SS Tubing New and swung at 6626' with 1-3' perforated nipple on bottom bull plugged and 1-4' and 1-6' sub on top. Displaced mud with 150 barrels oil.

Witnessed by **K. V. Stephenson** **Amerada Petroleum Corporation** **Foreman**
 Name Company Title

Subscribed and sworn before me this _____

I hereby swear or affirm that the information given above is true and correct.

7th. day of **August**, 19 **47**

Name **Walter James**

Position **Farm Boss**

Representing **Amerada Petroleum Corporation**
 Company or Operator

My commission expires **My Commission Expires May 9, 1948**

Address **Drawer D, Monument, New Mexico**

Remarks: **APPROVED**

Date **AUG 11 1947**

Roy Yarbrough
 Name
OIL & GAS INSPECTOR
 Title