


## OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

# DUPLICATE MISCELLANEOUS REPORTS ON WELLS



Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		Report on Plugging Back Well	X

September 22, 1947

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the \_\_\_\_\_

Amerada Petroleum Corporation State DA Well No. 4 in the \_\_\_\_\_  
Company or Operator Lease  
NE 1/4 SE 1/4 of Sec. 16, T. 21S, R. 37E, N. M. P. M.,  
Drinkard Field, Lea County.

The dates of this work were as follows: September 18, 19, 20, 21, 1947.

Notice of intention to do the work was (~~was not~~) submitted on Form C-102 on September 18 1947  
and approval of the proposed plan was (~~was not~~) obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

6641' Drilled Out Depth. Ran Baker Model K Cement Retainer and set at 6595'. Spotted 10 sacks of El Toro Cement and reversed out at 6582'. Re-cemented with 15 sacks of Incor Cement, used tubing flush of 25 barrels of mud and pulled up to 6582' and reversed out. Perforated with Lane Wells with 24 holes from 6567' to 6573'. Re-perforated with Lane Wells from 6528' to 6582', 216 holes. Ran 210 joints of 2" EUE, 4.7#, J-55, R-2, 8-RT, SS Tubing New and swung at 6577' with 1-3' perforated nipple on bottom bull plugged and 1-8' sub on top. Displaced mud with 150 barrels of oil and swabbed 150 barrels of oil into pits. Turned into tanks at 1:00PM, 9-21-47 and in 10 hours swabbed 56.15 bbls. pipe line oil. Shut in 11:PM, 9-21-47

Witnessed by K. V. Stephenson Amerada Petroleum Corporation Foreman  
Name Company Title

Subscribed and sworn before me this \_\_\_\_\_

I hereby swear or affirm that the information given above is true and correct.

22nd. day of September, 19 47

Name Ray Garbrosky

Position Asst. Dist. Supt.

Representing Amerada Petroleum Corporation  
Company or Operator

My commission expires By Commission Expires May 9, 1948

Address Drawer D, Monument, New Mexico

Remarks:

APPROVED  
SEP 25 1947

Date \_\_\_\_\_

Ray Garbrosky  
Name  
OIL & GAS INSPECTOR  
Title