

;



Sumbit this report in triplicate to the Oil Conservation Commission or its proper agent within ten the specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGIN	NNING DRILLING O		REFURI	ON REPAIRIN	G WELL	
REPORT ON RESUL' ICAL TREATMEN	T OF SHOOTING OR OT OF WELL	CHEM-		ON PULLING ERING CASING		WISE
REPORT ON RESU SHUT-OFF	LT OF TEST OF C.	ASING	REPORT	ON DEEPENIN	IG WELL	
REPORT ON RESUL	T OF PLUGGING OF	WELL				
	Sept	tember 16.	. 1947	Konus	ent. New	Mexi co
OIL CONSERVATIO SANTA FE, NEW M Gentlemen:	N COMMISSION,	-	Date			Place
Following is a report of Amerada Petro	on the work done and t	the results ob 1	A . .			4 in the
Compan	y or Operator		Lease	w en	NO	in the
NET SET	of Sec	. 16	218	R	37 E	, N. M. P. M.,
Drinkard	Field,	-				
						County.
	k were as follows:	-				
Notice of intention to	do the work was (Ma	actuatio subm	itted on Form C-	102 on Sep	tember 13	19.47
and approval of the p	proposed plan was 💭	secold obtai	ined. (Cross out	incorrect words	s.)	
	DETAILED ACCOUN	и ог 🕅 ан	V DONE AND DI		NED	
with tubin casing wit Perforated 6641*. Ran	h, Lime; 6641 B g and 4-3/4" bit h 1000# for 30 m $5\frac{1}{2}$ " casing with 212 joints of 2	Drilled ou t and dril dinutes be Lane Wel 2" EUE, 4.	t Depth. Nip led out ceme fore and aft is with a to .7#. R-2. 8-R	pled up 5 ¹ / ₂ " nt from 647 er drilling tal of 164 T. SS Tubin	Casing, 4 to 664 ; cement a shots from K New and	l'. Tested nd was OK. m 6600' to swung at
with tubin casing wit Perforated 6641*. Ran 6637* with Displaced	h, Lime; 6641 B ag and 4-3/4" bit h 1000# for 30 m $5\frac{1}{2}$ " casing with 212 joints of 2 1-3" perforated mud with 150 bar	brilled out t and dril dinutes be a Lane Wel 2ª EUE, 4. i nipple o rels of o	t Depth. Nip led out ceme fore and aft is with a to 7#, R-2, 8-R on bottom bul	pled up 52" int from 647 er drilling tal of 164 T, SS Tubin l plugged a	Casing, 4 to 664 cement a shots fro g New and nd 1-4 n	l'. Tested nd was OK. m 6600' to swung at
with tubin casing wit Perforated 6641°. Ran 6637° with	h, Lime; 6641 B g and 4-3/4" bit h 1000# for 30 m 5 ¹ / ₂ " casing with 212 joints of 2 1-3" perforated mud with 150 bar V. Stephenson	brilled out t and dril dinutes be a Lane Wel 2ª EUE, 4. i nipple o rels of o	t Depth. Nip led out ceme fore and aft is with a to 7#, R-2, 8-H on bottom bul oil.	pled up 52" int from 647 er drilling tal of 164 T, SS Tubin l plugged a	Casing, 4 to 664 cement a shots fro g New and nd 1-4 n	l'. Tested nd was OK. m 6600' to swung at ipple on top Foreman
with tubin casing wit Perforated 6641*. Ran 6637* with Displaced	h, Lime; 6641 B ag and 4-3/4" bit h 1000# for 30 m $5\frac{1}{2}$ " casing with 212 joints of 2 1-3" perforated mud with 150 bar	brilled out t and dril dinutes be a Lane Wel 2ª EUE, 4. i nipple o rels of o	t Depth. Nip led out ceme fore and aft is with a to 7#, R-2, 8-H on bottom bul oil.	pled up 52" int from 647 er drilling tal of 164 T, SS Tubin l plugged a	Casing, 4 to 664 cement a shots fro g New and nd 1-4 n	l'. Tested nd was OK. m 6600' to swung at ipple on top
with tubin casing wit Perforated 6641 ¹ . Ran 6637 ¹ with Displaced	h, Lime; 6641 B g and 4-3/4" bit h 1000# for 30 m 5 ¹ / ₂ " casing with 212 joints of 2 1-3" perforated mud with 150 bar V. Stephenson	brilled out t and dril dinutes be a Lane Wel 2ª EUE, 4. i nipple o rels of o	t Depth. Nip led out ceme ofore and aft is with a to 7#, R-2, 8-R on bottom bul oil.	pled up 5 ¹ / ₂ " ant from 647 er drilling tal of 164 T, SS Tubin l plugged a leum Corpor mpany	Casing, 4 to 664 cement a shots fro g New and nd 1-4 n	l'. Tested nd was OK. m 6600' to swung at ipple on top Foreman
with tubin casing wit Perforated 6641 ¹ . Ran 6637 ¹ with Displaced	h, Lime; 6641 B g and 4-3/4" bit h 1000# for 30 m 5 2 casing with 212 joints of 2 1-3 perforated mud with 150 bar V. Stephenson Name	brilled out t and dril dinutes be a Lane Wel 2ª EUE, 4. i nipple o rels of o	It Depth. Nip led out ceme ofore and aft is with a to 7#, R-2, 8-R on bottom bul oil.	pled up 5 ¹ / ₂ " ant from 647 er drilling tal of 164 T, SS Tubin l plugged a leum Corpor mpany	Casing, 4 to 664 cement a shots fro g New and nd 1-4 n	l'. Tested nd was OK. m 6600' to swung at ipple on top <u>Foremen</u> Title
with tubin casing wit Perforated 6641:. Ran 6637! with Displaced : Witnessed by <u>K.</u> Subscribed and swo <u>16th.</u> day of	h, Lime; 6641 B g and 4-3/4" bit h 1000# for 30 m 5½" casing with 212 joints of 2 1-3' perforated mud with 150 bar V. Stephenson Name	rilled out t and dril dinutes be Lane Wel 2" RUE, 4. i nipple o rels of o	it Depth. Nip led out ceme of ore and aft ls with a to 7%, R-2, 8-R on bottom bul oil. I hereby swear is true and cor Name	pled up 5 ¹ / ₂ " ant from 647 er drilling tal of 164 T, SS Tubin l plugged a leum Corpor mpany	Casing, 4º to 664 5 cement a shots fro g New and nd 1-4º n ation the informat	l'. Tested nd was OK. m 6600' to swung at ipple on top <u>Foremen</u> Title
with tubin casing wit Perforated 6641:. Ran 6637! with Displaced : Witnessed by K. Subscribed and swo 16th. day of	h, Lime; 6641' D g and 4-3/4" bit h 1000# for 30 m 5 ¹ / ₂ " casing with 212 joints of 2 1-3' perforated mud with 150 bar V. Stephenson Name rn before me this September	rilled out t and dril dinutes be Lane Wel 2" RUE, 4. i nipple o rels of o	it Depth. Nip led out ceme for e and aft ls with a to 7%, R-2, 8-R on bottom bul oil. Merada Petro Con I hereby swear is true and cor Name Position	pled up 52" int from 647 er drilling tal of 164 T, SS Tubin l plugged a leum Corpor mpany or affirm that rect.	Casing, 4' to 664 ; cement a shots fro g New and nd 1-4' n ation the informat	1'. Tested rd was OK. m 6600' to swung at ipple on top Foreman Title tion given above
with tubin casing wit Perforated 6641:. Ran 6637! with Displaced : Witnessed by K. Subscribed and swo 16th. day of	h, Lime; 6641' D g and 4-3/4" bit h 1000# for 30 m 52" casing with 212 joints of 2 1-3' perforated mud with 150 bar V. Stephenson Name rn before me this September 15 Maile Juff Notars	rilled out and dril ainutes be lane Wel " RUE, 4. i nipple o rels of o 	it Depth. Nip led out ceme for e and aft is with a to 7%, R-2, 8-R on bottom bul oil. Merada Petro Con I hereby swear is true and cor Name Position Representing	pled up 52" int from 647 er drilling tal of 164 T, SS Tubin l plugged a leum Corpor mpany or affirm that rect.	Casing, 4 to 664 cement a shots fro g New and nd 1-4 n the informat the informat Supt. Coperator	l'. Tested nd was OK. m 6600' to swung at ipple on top <u>Foreman</u> Title tion given above
with tubin casing wit Perforated 6641*. Ran 6637* with Displaced : Witnessed by <u>K</u> . Subscribed and swo 16th. day of UI	h, Lime; 6641' D g and 4-3/4" bit h 1000# for 30 m 52" casing with 212 joints of 2 1-3' perforated mud with 150 bar V. Stephenson Name rn before me this September 15 Maile Juff Notars	rilled out and dril ainutes be lane Wel BUE, 4. i nipple o rels of o A 	it Depth. Nip led out ceme for e and aft is with a to 7%, R-2, 8-R on bottom bul oil. Merada Petro Con I hereby swear is true and cor Name Position Representing	pled up 52" int from 647 er drilling tal of 164 T, SS Tubin l plugged a leum Corpor mpany or affirm that rect. Asst. Blat. Company or	Casing, 4 to 664 cement a shots fro- g New and nd 1-4 n the informat the informat Supt. Coleum Co Operator	l'. Tested rd was OK. m 6600' to swung at ipple on top Foreman Title tion given above Foreman New Mexico Name NSPECTOR
with tubin casing wit Perforated 6641 [*] . Ran 6637 [*] with Displaced in Witnessed by <u>K</u> . Subscribed and swo 16th. day of <i>U</i> .	h, Lime; 6641 B g and 4-3/4" bit h 1000# for 30 m 52" casing with 212 joints of 2 1-3" perforated mud with 150 bar V. Stephenson Name rn before me this September It Maile Juff Notary bires Dy Commission Ervires 36	rilled out and dril ainutes be lane Wel BUE, 4. i nipple o rels of o A 	it Depth. Nip led out ceme for e and aft is with a to 7%, R-2, 8-R on bottom bul oil. Merada Petro Con I hereby swear is true and cor Name Position Representing	pled up 52" int from 647 er drilling tal of 164 T, SS Tubin l plugged a leum Corpor mpany or affirm that rect. Asst. Blat. Company or	Casing, 4 to 664 cement a shots fro- g New and nd 1-4 n the informat the informat Supt. Coleum Co Operator	l'. Tested nd was OK. m 6600' to swung at ipple on top Foreman Title tion given above
with tubin casing wit Perforated 6641 [*] . Ran 6637 [*] with Displaced in Witnessed by <u>K</u> . Subscribed and swo 16th. day of <i>U</i> .	h, Lime; 6641 B g and 4-3/4" bit h 1000# for 30 m 52" casing with 212 joints of 2 1-3" perforated mud with 150 bar V. Stephenson Name rn before me this September It Maile Juff Notary bires Dy Commission Ervires 36	y Public	it Depth. Nip led out ceme of or e and aft is with a to 7%, R-2, 8-R on bottom bul oil. Merada Petro Con I hereby swear is true and cor Name Position Representing Address	pled up 52" int from 647 er drilling tal of 164 T, SS Tubin l plugged a leum Corpor mpany or affirm that rect. Asst. Blat. Company or	Casing, 4 to 664 cement a shots fro- g New and nd 1-4 n the informat the informat Supt. Coleum Co Operator	l'. Tested rd was OK. m 6600' to swung at ipple on top Foreman Title tion given above Foreman New Mexico Name NSPECTOR
with tubin casing wit Perforated 6641 [*] . Ran 6637 [*] with Displaced in Witnessed by <u>K</u> . Subscribed and swo 16th. day of <i>U</i> .	h, Lime; 6641 B g and 4-3/4" bit h 1000# for 30 m 52" casing with 212 joints of 2 1-3" perforated mud with 150 bar V. Stephenson Name rn before me this September It Maile Juff Notary bires Dy Commission Ervires 36	y Public	it Depth. Nip led out ceme for e and aft is with a to 7%, R-2, 8-R on bottom bul oil. Merada Petro Con I hereby swear is true and cor Name Position Representing	pled up 52" int from 647 er drilling tal of 164 T, SS Tubin l plugged a leum Corpor mpany or affirm that rect. Asst. Blat. Company or	Casing, 4 to 664 cement a shots fro- g New and nd 1-4 n the informat the informat Supt. Coleum Co Operator	l'. Tested rd was OK. m 6600' to swung at ipple on top Foreman Title tion given above rporation New Mexico