

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

DUPLICATE

MISCELLANEOUS REPORTS ON WELLS

OCT 2 1947
RECEIVED
HOBBS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	X	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

September 29, 1947

Date

Hobbs, New Mexico

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the
Stanolind Oil & Gas Company State C Tract 12 Well No. 2 in the
 Company or Operator Lease

NW/4 of Sec. 16, T. 21-S, R. 37-E, N. M. P. M.,
Drinkard Field, Lea County.

The dates of this work were as follows:

Notice of intention to do the work was (was ~~not~~) submitted on Form C-102 on Sept. 20 1947
 and approval of the proposed plan was (was ~~not~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

On September 20th, at 6:00 P.M., 24 hours had elapsed since setting 316 feet of 13-3/8" OD 54.5# and 48# casing in subject well and cemented with 325 sacks cement to be used as surface string. At this time, casing shut-off was tested as follows:

A pressure of 750# was built up and held for thirty minutes, and as casing tests were O.K., cement plug was drilled and a pressure of 750# again was built up and held for thirty minutes. As this test was O.K., drilling operations were resumed.

Witnessed by L.L. Martin Stanolind Oil & Gas Co. Hd. Rslt.
 Name Company Title

Subscribed and sworn before me this 30th

I hereby swear or affirm that the information given above is true and correct.

day of September, 1947Name Reed J. HenningsenPosition Field Supt.Representing Stanolind Oil & Gas Co.
Company or OperatorMy commission expires 2-23-50Address Box F; Hobbs, N.M.

Remarks:

APPROVED

Reed J. Henningsen
 Name
 OIL & GAS INSPECTOR
 Title

OCT 2 1947