

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER) Dual Completion	X

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico
(Place)

July 10, 1959
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the SUNRAY MID-CONTINENT OIL COMPANY

State Land "15" Well No. 2 in N
(Company or Operator) Lease (Unit)
SE 1/4 SW 1/4 of Sec. 16, T. 21S, R. 37E, NMPM, Blinebry Pool
(40-acre Subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Move in pulling unit. Kill well with oil and pull tubing. Round trip casing scraper. Set Baker retrievable plug at 6000'. Perforate at following depths with 2 holes per foot: 5613-18', 5622-25', 5645-50', 5665-70', 5685-90', 5705-10', 5727-32', 5750-55', 5768-72', 5785-90', 5803-10', 5830-35', 5840-42', 5848-53', 5870-75', 5888-91'. Run 3-1/2" tubing with packer and acidize with 4000 gallons 15% LTNE acid in 4 stages using 50 balls after first stage, 50 balls after second stage, and 25 to 48 balls after third stage depending on pressures. Let pressure bleed off to drop balls off perforations. Fracture with 20,000 gallons oil and 20,000# sand in 4 stages using same number of balls as was used in acid job. Wash out sand and rubber balls and pull retrievable bridge plug. Run Baker Model "D" packer on 2" tubing with GOT sleeve, set packer at 6505' and swab in both zones, producing Drinkard through 2" tubing, and Blinebry through tubing-casing annulus. (Administrative approval has been requested for the dual completion)

Approved....., 19.....
Except as follows:

Approved
OIL CONSERVATION COMMISSION

By.....
Title.....

SUNRAY MID-CONTINENT OIL COMPANY

By.....
Position.....

District Engineer
Send Communications regarding well to:

Name Sunray Mid-Continent Oil Company
Address P.O. Box 128, Hobbs, New Mexico