

Form 9-331
Dec. 1973Form Approved.
Budget Bureau No. 42-R1424UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other

2. NAME OF OPERATOR

Conoco Inc.

3. ADDRESS OF OPERATOR

P.O. Box 460 Hobbs, N.M. 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980' FSL & 660' FEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☒
☐
☐
☐RECEIVED
OCT 22 1979
U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

5. LEASE

LC-032096(a)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

N.M.F.U.

8. FARM OR LEASE NAME

Lockhart A-17

9. WELL NO.

2

10. FIELD OR WILDCAT NAME

Blinberry Oil & Gas / Eumont

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 17, T-21S, R-37E

12. COUNTY OR PARISH

Lea

13. STATE

N.M.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3470' DF.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

MIRU 7-24-79 & Killed well. Spot 12 bbls. 15% HCl-NE acid from 5975-55:
Perf. Blinberry formation @ 5556', 70', 82', 97', 5620', 26', 57', 66', 90', 5703', 13',
47', 58', 87', 5800', 5832', 38', 94', 5916', 28', 48' w/ 1 JSPP. Pumped
4200 gal. 15% HCl-NE acid & flushed. Frac'd w/ 74000
gal. gelled water, 154,000# 20/40 sand. w/ H w/ production
equipment. SN @ 5460' & pkr. @ 5490'. CO 76g. & swabbed
well. Returned to production & testing.

Subsurface Safety Valve: Manu. and Type _____

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

John A. Butterfield

TITLE

Admin. Supervisor

10/19/79

(This space for Federal office use)

APPROVED BY _____

CONDITIONS OF APPROVAL, IF ANY:

USGS-5

NMFU-4

FILE

*See Instructions on Reverse Side

RECEIVED

OCT 14 1961

O.C.D., HOBBS, OFFICE