



UNITED STATES DEPARTMENT OF THE INTERIOR



	INTENTION TO DRILL		SUBSEQUENT REPO	ORT OF WATER SHU	T-0FF	
OTICE OF	INTENTION TO CHANGE PLANS		SUBSEQUENT REPO	RT OF SHOOTING	OR ACIDIZING	
OTICE OF	INTENTION TO TEST WATER SHUT-	OFF	SUBSEQUENT REPO	RT OF ALTERING O	ASING	
OTICE OF	INTENTION TO RE-DRILL OR REPAI	R WELL	SUBSEQUENT REPO	RT OF RE-DRILLIN	G OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE			SUBSEQUENT REPORT OF ABANDONMENT.			
IOTICE OF INTENTION TO PULL OR ALTER CASING			SUPPLEMENTARY WELL HISTORY			
NOTICE OF	INTENTION TO ABANDON WELL		e constant de la cons	mines of	*************	
	(INDICATE ABOVE	BY CHECK MARK NAT	TURE OF REPORT, NOT		A)	
_			·····		3 ;	, 19 <u></u>
ell No.	Lockhar's located 23	ft. from	S line and	ft. from	W line of sec.	
5¥/4	800. 17 ee, and Sec. No.) (T-21-6	B-37-E	(Meridian)	 	
	66, and 566. No.)	Isa	nBo)	(Meridian)	lex1ee	
	(Field)	(County or Su	ıbdivision)	(Sta	ite or Territory)	
tate names	of and expected depths to objective	e sands; show sizes, v	OF WORK	of proposed casing	; indicate mudding jok	os, cement-
ha #=		points, and all other		•	Man at Asso.	_
29/58	Note in 180 and here	r case trum ine plan wit	h 1000d aced	pe straight for	Plug et 6550' r 15 minutes.	Test
	in necessite dress	-An house and	_			
ten bed		st intervals	1 6106-6116	, 6121-619	1, 6200-6210,	6251-
30/56	4200_4200 with	two jet sho				
30/76			41. 48 44			
b des					to bee the bee	10000
/1/58			en au, coo gi	Heriman	processo 3400	
1/58	Prestured Table personal, Average presided average injection	nsure 3200/ Non rute 17	equare inch. BPM. Recoi	Heximus lexed load	processo MCC ell and refis	ed oil
b las	Prestured Table personal, Average presided average injection	nsure 3200/ Non rute 17	equare inch. BPM. Recoi	Heximus lexed load	processo 3400	ed oil

T:41.

