

NEW MEXICO OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL		NOTICE OF INTENTION TO PLUG WELL	
NOTICE OF INTENTION TO DEEPEN WELL			

Place

Date

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico.

Gentlemen:

Following is a notice of intention to do certain work as described below at the

Neville G. Penrose Inc.

Company or Operator

Lease

Well No. **I** inof Sec. **17**, T. **22S**, R. **37E**, N. M. P. M.,

Field.

Las County.

FULL DETAILS OF PROPOSED PLAN OF WORK

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION

We propose to drill 17½" hole, run and cement 195 Ft. of 133/8" - 48# casing using enough cement to circulate back to surface.

After allowing 48 hrs. set time on cement, pipe will be tested and plug drilled.

After plug is drilled cement around shoe also will be tested with 1000# pump pressure.

ILLEGIBLE

Approved _____, 19____
except as follows:

Neville G. Penrose Inc.

Company or Operator

By _____

Position **Prod. Supt.**

Send Communications regarding well to

Name **Neville G. Penrose Inc.**Address **1814 Fair Bldg.,****Fort Worth, Texas**

OIL CONSERVATION COMMISSION,

By

Title

OIL & GAS INSPECTOR

Levitt & Sons, Inc.

375

17

and

- 48. Concerning existing cement to be used in the future, it is proposed to drill 17 1/2" holes, with a cement plug 12" in length.

After allowing 48 hrs. set time on cement, the holes tested and plug drilled. After plug is drilled cement crown will be tested for 100% pressure.

Levitt & Sons, Inc.

and

Levitt & Sons, Inc.

17 1/2" in dia.

12" in length