

Pulled tubing. Tagged up at 5890'. Sand pumped to 6140'. Perforated additional Elinebry 5585, 94; 5633, 39, 47, 59, 67, 85, 94; 5700, 10, 34, 38, 44, 94; 5805; 5942, 55, 66, 75, 82, 91; 6004, 11, and 29'. (25 holes. Set BP @ 6100', packer at 5474'. Treated with 1,500 gals. 15% NE Acid and 25 ball sealers. Fraced with 45,000 gals. gelled brine and 66,000# 20-40 sand in 3 stages. Used 750 gals. 15% Acid between stages and 3400# Benzoic Acid Flakes and 2100# Salt in 4 block stages. Total load to recover 2178 BLW. Swabbed back 137 BTF. Layed down 3-1/2" frac tubing and packer. Tagged sand fill @ 6035'. Cleaned sand out to BP. Recovered BP. Set 2" tubing @ 5543, SN @ 5535', packer @ 5536'. Swabbed well in and put on intermitter.

1×. (h	erens certify that th	e information above is true and corn. ORIGINAL SIGNED BY:	plete to the best of a			
STONES	C.L. Wade:			SUPERINTENDENT	JULY 30, 1975	
		Oria Algred By	. <u></u> .		• 7 1 	
48-2- ·	·	nyan	т., с. Е. <u></u>	·	54.5 - F	

COND. IT NS OF AFPROVAL, IF ANY:

;

. •

> and the second sec

A standard for the second secon