

DUPLICATE

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

RECEIVED
JUN 1 1948
HOBBS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL	X	REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	X	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		Report of squeezing off gas	X

May 31st, 1948, Hobbs, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____
Tide Water Associated Oil Company **Percy Hardy** Well No. **2** in the

Company or Operator **SW/4 of SE/4** of Sec. **17**, T. **21-S**, R. **37-E**, N. M. P. M.,
Drinkard Field, **Lea** County.

The dates of this work were as follows: **5-2-48, 5-5-48, 5-9-48, 5-11-48**

Notice of intention to do the work was ~~(was not)~~ submitted on Form C-102 on **May 1st** 19 **48**
and approval of the proposed plan was (was not) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Set **5 1/2"** Casing at **6650'** w/ **500 sks.**, casing was tested with **1200#** before drilling plug and held for **30 minutes** for a satisfactory shut off. Drilled plug to **6650'**, perforated **5 1/2"** casing from **6625'** to **6650'** with **200 - 1/2"** holes. Acidized with **500 gallons** by Dowell. After acid had **2,000,000 cu ft** of gas and attempted to shut it off by squeezing top **2 feet** of perforations with Dowell Plastic, and got partial shut off.

Official test on **5-26-48**: **43.28 bbls** of oil in **24 hours**, on **5/32"** choke and a Gas-Oil ratio of **4932-1**.

Witnessed by **H.G. Wesberry** **Tide Water Associated Oil Company** **Foreman**
Name Company Title

Subscribed and sworn before me this

31st day of **May** 19 **48**

[Signature]
Notary Public

My Commission Expires September 15, 1951

My commission expires

I hereby swear or affirm that the information given above is true and correct.

Name *[Signature]*

Position **Foreman**

Representing **Tide Water Associated Oil Company**

Company or Operator

Address **Drawer KK, Hobbs, New Mexico**

Remarks:

APPROVED

JUN 1 1948

Name

[Signature]
Title **Oil & Gas Inspector**

