

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK	X	NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER) <u>Recomplete as</u>	X

Bumont Gas well

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico

June 14, 1956

(Place)

(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Gulf Oil Corporation H. T. Mattern "C"

Well No. **3** in **L** (Unit)NW $\frac{1}{4}$ SW $\frac{1}{4}$ of Sec. **18**, T. **21S**, R. **37E** NMPM, Penrose Skelly Pool

(40-acre Subdivision)

Lea

County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

It is proposed to plug back and fracture treat as follows:

1. Pull tubing and rods.
2. Run east iron cement retainer on tubing, set retainer at approximately 3690'.
3. Squeeze cement the open hole interval 3700-3814'. Leave approximately 10' of cement on top of retainer.
4. Perforate interval from approximately 3550-3645'.
5. Run 2 7/8" tubing and hookwall packer with hydraulic holddown. Treat perforations with 250 gallons cleanout acid. Treat formation with 10,000 gallons low gravity oil with 1# sand per gallon.
6. Pull 2 7/8" tubing, packer and holddown. Rerun 2 3/8" tubing, return well to production.

Approved....., 19.....
Except as follows:Approved
OIL CONSERVATION COMMISSION

By.....

Title.....

Gulf Oil Corporation

Company or Operator

By.....

Position..... Area Supt. of Prod.

Send Communications regarding well to:

Name..... Gulf Oil Corp.

Address..... Box 2167, Hobbs, N.M.