

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - I" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator SOHIO PETROLEUM COMPANY		8. Farm or Lease Name Alves
3. Address of Operator P. O. Box 3000, Midland, Texas 79701		9. Well No. 1
4. Location of Well UNIT LETTER H , 1980 FEET FROM THE North LINE AND 660 FEET FROM THE East LINE, SECTION 18 TOWNSHIP 21S RANGE 37E NMPM.		10. Field and Pool, or Wildcat Penrose-Skelly, Grayburg
15. Elevation (Show whether DF, RT, GR, etc.) 3482' GR		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

This well was temporarily abandoned 5-5-63; and again 6-11-74, uneconomical to produce.
PROPOSED WORK:
Set 100' cement plug above 3692-3723' perforations.
Cut off 7" casing at about 1500'.
Place 100' cement plug 1450-1550' (50' in and 50' out of casing).
Place 100' cement plug above salt, 1240'-1340'.
Place 100' cement plug 50' in and 50' out of surface, 112-212'.
Place 10 sack plug at surface.
Mud laden fluid will be placed between plugs.
This work will start on or before 10-1-75.

Expires 12/1/75

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED J.H. Walters J.H. Walters TITLE District Superintendent
Midland District DATE December 4, 1974

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: