

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico				Northwestern New Mexico			
T. Anhy	1136	T. Canyon		T. Ojo Alamo		T. Penn. "B"	
T. Salt	1320	T. Strawn		T. Kirtland-Fruitland		T. Penn. "C"	
B. Salt	2630	T. Atoka		T. Pictured Cliffs		T. Penn. "D"	
T. Yates	2820	T. Miss		T. Cliff House		T. Leadville	
T. 7 Rivers		T. Devonian		T. Menefee		T. Madison	
T. Queen	3452	T. Silurian		T. Point Lookout		T. Elbert	
T. Grayburg		T. Montoya		T. Mancos		T. McCracken	
T. San Andres		T. Simpson		T. Gallup		T. Ignacio Otzte	
T. Glorieta	5135	T. McKee		Base Greenhorn		T. Granite	
T. Paddock		T. Ellenburger		T. Dakota		T.	
T. Blinbry		T. Gr. Wash		T. Morrison		T.	
T. Tubb	6150	T. Delaware Sand		T. Todilto		T.	
T. Drinkard		T. Bone Springs		T. Entrada		T.	
T. Abo		T.		T. Wingate		T.	
T. Wolfcamp		T.		Chinle		T.	
T. Penn		T.		T. Permain		T.	
T. Cisco (Bough C)		T.		T. Penn "A"		T.	

OIL OR GAS SANDS OR ZONES

No. 1, from.....to..... No. 3, from.....to.....
 No. 2, from.....to..... No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
0	380	380	Red bed	4562	4680	118	Lime
380	439	59	Red bed, shale	4680	4775	95	Lime, shale
439	1061	622	Red bed	4775	5302	527	Lime
1061	1356	295	Anhy, gyp.	5302	5422	120	Lime, sand
1356	2167	811	Anhy, salt	5422	5711	289	Lime
2167	2192	25	Anhy, salt, sand	5711	5779	68	Lime, shale
2192	2368	176	Anhy, salt	5779	5901	122	Lime
2368	2463	95	Anhy, sand	5901	5941	40	Lime, sand
2463	2605	142	Anhy, gyp	5941	6053	212	Lime
2605	2636	31	Anhy	6053	6128	75	Lime, sand
2636	2860	224	Anhy, sand	6128	6217	89	Lime
2860	3527	667	Lime, sand	6217	6260	43	Lime, sand
3527	3900	373	Lime	6260	6359	99	Lime
3900	4076	176	Sand	6359	6408	49	Dolo Lime
4076	4550	474	Lime, sand	6408	6754	346	Lime
4550	4562	12	Lime shale				