Form	9-831 a
(Feb	. 1951)

	l		
1			 
		!	
-		,	!
1	ŀ		
			'
	l		

## (SUBMIT IN TRIPLICATE)

Land Offic	N	ata ?s,	8. 2.	
Lease No.	105	ruces	032591	e)
Unit				

## UNITED STATES **DEPARTMENT OF THE INTERIOR** GEOLOGICAL SURVEY

			I
NOTICE OF INTENTION TO DRILL NOTICE OF INTENTION TO CHANGE PLAI		BSEQUENT REPORT OF WATER SHUT-OFF BSEQUENT REPORT OF SHOOTING OR ACIDIZING .	
NOTICE OF INTENTION TO TEST WATER		BSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR NOTICE OF INTENTION TO SHOOT OR A		BSEQUENT REPORT OF RE-DRILLING OR REPAIR BSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALT			
NOTICE OF INTENTION TO ABANDON WE	ELL.		
(INDICATE	ABOVE BY CHECK MARK NATURE O	OF REPORT, NOTICE, OR OTHER DATA)	
		coveres with	, 19. <b>57</b>
'ell No. is located	ر ح	line and $1$ 50 ft. from $\left\{egin{array}{c} \mathbf{E} \\ \mathbf{W} \end{array}\right\}$ line of	sec. 19
(14 Section 19	(Twp.) (Range)		
arose facily a ment	(Twp.)	(Meridian)	
(Field)	(County or Subdivis	-	
ne elevation of the derrick fl	oor above sea level is	<b>514</b> ft.	
	DETAILS OF	WORK	
tate names of and expected depths to ob	ojective sands; show sizes, weight ing points, and all other impo	ts, and lengths of proposed casings; indicate mudo ortant proposed work)	ding jobs, cement-
Held	" 0.3. 23# New 01	l string at ale of 3702'. (	sented v
LYNN YARGO, OT L		nt. Job complete 5:00 F.A.	
wap and plug method wi			
ump and plug method wi an temperature survey		for a sinutes, Job to k.	Hiteb fill
ump and plug nethod vi an temperature survey rilled cement - tested	casing with 1000g	for A minutes. Job v. t. i platice in support the and . :	
ump and plug method wi an temperature survey rilled cement - tested -1/4" hole abuse to 38	casing with 1000g		
ump and plug method wi am temperature survey rilled cement - tested -1/4" hole abuse to 38	casing with 1000g		
ump and plug method wi am temperature survey rilled cement - tested -1/4" hole abuse to 38	casing with 1000# 00 g for tush com	plutica in sement des and , e	
ump and plug method wi am temperature survey rilled cement - tested -1/4" hole abuse to 38	casing with 1000# 00 g for tush com	plutica in sement des and , e	
ump and plug method wi am temperature survey rilled cement - tested -1/4" hole abuse to 38	casing with 1000# 00 g for tush com		
ump and plug method wi an temperature survey rilled cement - tested -1/4" hole abused to 38 kelly vil.	easing with 1000# 000 g for their com	plutica in sement des and , e	er l'e <b>po</b>
I understand that this plan of work m	casing with 1000 grows on the company of the compan	GIBLE  y the Geological Survey before operations may be	er l'e <b>po</b>
an temperature survey srilled cement - tested >-1/4" hole abused to 38 kelly til.	CO E for Ausi com	GIBLE  y the Geological Survey before operations may be	er l'e <b>po</b>

	nd that this plan of work must receive approval in writin	g by the Geological Survey before operations may be commenced.
Address	ε.υ. ε <b>οχ 65</b> 5	
	Closes, Texas	By R. F. L. Long
		By Arrator Title