

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		Report on Plugging Back	X

April 11, 1948

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Amerada Petroleum Corporation

J. G. Randle

Well No. 1 in the

Company or Operator

Lease

SW 1/4 NE 1/4

of Sec. 20

T. 21S

R. 37E

N. M. P. M.,

Brunson

Field, Lea

Lea

County.

The dates of this work were as follows:

April 9, 10, 11, 1948

Notice of intention to do the work was (~~received~~) submitted on Form C-102 on April 9, 1948 and approval of the proposed plan was (~~received~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

6575' Plugged Back Depth. Set Baker Bridging Plug at 6675' and filled hole with 155 bbls. water. Plugged back with 15 sacks of cement from 6675' to 6575' and reversed out about 2 1/2 sx. cement at 1:30AM, 4-10-48. Drilled out cement to 6650'. Perforated with McCullough from 6520'-6590' and 6605'-6645', 440 holes. Ran 209 joints of 2-3/8" OD, 4.7# Tubing and Guiberson Packer with 1-3' perf. sub on bottom bull plugged, 1-4' handling sub and 1-6', 1-4', 1-8' subs on top. Packer set at 6443' with bottom of tbg. at 6638'. Displaced water with 155 bbls. oil.

Witnessed by D. W. Gordon

Amerada Petroleum Corporation

Farm Boss

Name

Company

Title

Subscribed and sworn before me this

I hereby swear or affirm that the information given above is true and correct.

11th. day of April 19 48

Name

Position

Asst. Dist. Supt.

Representing

Amerada Petroleum Corporation
Company or Operator

My commission expires

Address

Drawer D, Monument, New Mexico

Remarks:

Name

Title