

OIL CONSERVATION DIVISION
P. O. BOX 2038
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State ☐	Fee ☒
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - I" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒	GAS WELL ☐	OTHER ☐
--	-----------------------------------	--------------------------------

Name of Operator
Chevron U.S.A. Inc.

Address of Operator
P.O. Box 670 Hobbs, NM 88240

Location of Well

UNIT LETTER N 554 FEET FROM THE South LINE AND 2086 FEET FROM

THE West LINE, SECTION 20 TOWNSHIP 21S RANGE 37E N.M.P.M.

15. Elevation (Show whether DF, RT, GR, etc.)
3487

7. Unit Agreement Name

8. Farm or Lease Name
C.L. HARDY

9. Well No.
2

10. Field and Pool, or Wildcat
Drinkard

12. County
Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

ORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐
FORABLY ABANDON ☐	CHANGE PLANS ☐
OR ALTER CASING ☐	
OTHER <u>Sqz perfs; add Drinkard perfs, acidz & frac</u> ☒	

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐	ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOBS ☐	
OTHER ☐	

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

It is proposed to plug off the Paddock and Blinbry perforations (Blinbry - 5770-5907) (Paddock 5148-5226) by squeezing, drill out cmt and CIBP at 6431-86. Clean out to 6675', acidize open hole w/3500 gallons 15% NEFE HCL, swab, frac open hole w/19000 gallons 40# HPG gelled 8.6# BW and 25,500# 20/40 ottawa sand at 20BPM and 5000psi swab back, clean out to 6675'. Perf Drinkard w/4" guns, 2 SPF, 180° phase at 6526-28, 6538-40, 6551-53, 6560-62, 6575-77, 6585-87, total 24 shots, per zone. Acidize new perfs w/4000 gallons 15% NEFE HCL and 36 ballsealers, swab back and test. Return to production.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

L.K. Elmore TITLE Drilling Technical Assistant DATE November 2, 1988

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR

DATE NOV 04 1988

CONDITIONS OF APPROVAL, IF ANY: