

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

DUPLICATE

MISCELLANEOUS REPORTS ON WELLS

RECEIVED
SEP 25 1947
HOBBS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	9-5/8"	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

September 22, 1947 Hobbs, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____

Gulf Oil Corporation

Hardy

Well No. 2 in the _____

Company or Operator

Lease

SE SW

of Sec. 20

T. 21S

R. 37E, N. M. P. M.,

Drinkard

Field, Lea

County.

The dates of this work were as follows: Cemented September 19, 1947; tested September 21, 1947.

Notice of intention to do the work was ~~(was not)~~ submitted on Form C-102 on September 22, 1947and approval of the proposed plan was ~~(was not)~~ obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

The hole was washed down and the casing tested with 1250# pressure applied for 30 minutes. The plug was drilled and the casing tested with 1250# pressure applied for 30 minutes. Both tests were OK, and after approval of Mr. Yarbrough, State Oil and Gas Inspector, preparations were made to drill ahead.

Cement back of 9-5/8" casing is at 1315' per temperature survey.

Witnessed by G.O. Baysinger Gulf Oil Corporation Foreman
Name Company Title

Subscribed and sworn before me this _____

I hereby swear or affirm that the information given above is true and correct.

22nd day of September, 1947

Name Paul C. EvansPosition Act'g. District Supt.Representing Gulf Oil Corporation
Company or Operator

Notary Public

My commission expires 10-24-49

Address Box 1667, Hobbs, New Mexico

Remarks:

APPROVED
SEP 25 1947
Date _____

Ray Yarbrough
Name
OIL & GAS INSPECTOR
Title