

NEW MEXICO OIL CONSERVATION COMMISSION
SOUTHEAST NEW MEXICO PACKER LEAKAGE TEST

Operator Sunray DX Oil Company				Lease E. Elliott "B"		Well No. 1	
Location of Well	Unit D	Sec 20	Twp 21S	Rge 37E	County Lea		
	Name of Reservoir or Pool		Type of Prod (Oil or Gas)	Method of Prod Flow, Art Lift	Prod. Medium (Tbg or Csg)	Choke Size	
Upper Compl	Blinebry Oil		Oil	Flow	Casing c	-	
Lower Compl	Drinkard		Oil	Art. Lift	Tubing	-	

FLOW TEST NO. 1

Both zones shut-in at (hour, date): Drinkard - 9:30 AM 8-22-66, Blinebry - No Allowable

Well opened at (hour, date): 10:15 AM 8-23-66	Upper Completion	Lower Completion
Indicate by (X) the zone producing.....		X
Pressure at beginning of test.....	725	275
Stabilized? (Yes or No).....	Yes	Yes
Maximum pressure during test.....	725	275
Minimum pressure during test.....	725	50
Pressure at conclusion of test.....	725	50
Pressure change during test (Maximum minus Minimum).....	0	225
Was pressure change an increase or a decrease?.....	-	decrease
Well closed at (hour, date): 10:15 AM 8-24-66	Total Time On Production 24 hrs.	
Oil Production During Test: 2 bbls; Grav. 36.9	Gas Production 112 MCF; GOR 56,000	
Remarks		

FLOW TEST NO. 2

Well opened at (hour, date):	Upper Completion	Lower Completion
Indicate by (X) the zone producing.....		
Pressure at beginning of test.....		
Stabilized? (Yes or No).....		
Maximum pressure during test.....		
Minimum pressure during test.....		
Pressure at conclusion of test.....		
Pressure change during test (Maximum minus Minimum).....		
Was pressure change an increase or a decrease?.....		
Well closed at (hour, date)	Total time on Production	
Oil Production During Test: bbls; Grav.	Gas Production MCF; GOR	
Remarks Acreage presently dedicated to Blinebry Gas Unit therefore Blinebry Oil completion was not produced.		

I hereby certify that the information herein contained is true and complete to the best of my knowledge.

Approved New Mexico Oil Conservation Commission	Operator Sunray DX Oil Company
By [Signature]	By [Signature] B. F. Brawley
Title [Signature]	Title District Engineer
	Date August 29, 1966

SOUTHEAST NEW MEXICO PACKER LEAK TEST INSTRUCTIONS

1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Commission.
2. At least 72 hours prior to the commencement of any packer leakage test the operator shall notify the Commission in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized and for a minimum of two hours thereafter, provided however, that they need not remain shut-in more than 24 hours.
4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued until the flowing wellhead pressure has become stabilized and for a minimum of two hours thereafter, provided however, that the flow test need not continue for more than 24 hours.

5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the previously shut-in zone is produced.
7. All pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges, the accuracy of which must be checked with a deadweight tester at least twice, once at the beginning and once at the end, of each flow test.
8. The results of the above-described tests shall be filed in the appropriate District Office of the New Mexico Oil Conservation Commission on Southeast New Mexico Packer Leakage Test Form Revised 1-1-58 together with the original pressure recording gauge charts with which the deadweight pressures which were taken indicated thereon. In filing the aforesaid charts, the operator may construct a pressure versus time curve for each zone of each test, indicating thereon all pressure changes which may be reflected by the gauge charts as well as all deadweight pressure readings which were taken. If the pressure curve is submitted, the original chart must be permanently filed in the operator's office. Form C-116 shall also accompany the Packer Leakage Test report when the test period coincides with a gas-oil ratio test period.

99.113 6-11-58