

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER) Frac	X	NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico
(Place)

March 2, 1962
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Sunray Mid-Continent Oil Company J. G. Randle Well No. 1 in E
 (Company or Operator) (Lease) (Unit)
SW 1/4 NW 1/4 of Sec. 20, T. 21S, R. 37E, NMPM., Drinkard Pool
 (40-acre Subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
 (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

1. Move in pulling unit and load hole with crude as necessary.
2. Remove tbghd and install BOP. Lower tubing to bottom to check sand fill-up. Pull tbg out and run bit to clean out if necessary.
3. Run Baker FB packer on 3 1/2" tubing and set packer at approximately 6600'.
4. Frac Drinkard with 2,000 gal of 15% LTNE acid for spearheads and 20,000 gals refined oil using rock salt as pressures permit.
5. Leave well shut-in 24 hrs or until pressure bleeds off whichever is the shorter time. Pull 3 1/2" tubing and packer when pressure permits.
6. Run 2 3/8" tubing with seating nipple, mud anchor, and scalloped collar. Remove BOP and install tubinghead.
7. Swab well onto production, or if well will not flow, run rods and pump.

Approved....., 19.....
 Except as follows:

Approved
OIL CONSERVATION COMMISSION

By.....

Title.....

Sunray Mid-Continent Oil Company
 (Company or Operator)

By.....

Position.....
 District Engineer

Send Communications regarding well to:

Name..... C. T. McClanahan

Address..... Box 128 Hobbs, New Mexico