

DUPLICATE  
OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

# Miscellaneous Reports on Wells

RECEIVED  
JAN 4 1952  
OIL CONSERVATION COMMISSION  
HOBBS, NEW MEXICO

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<b>X</b>	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

January 3, 1952

Hobbs, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO.  
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the  
**ROSS SEARS**      **Wants**      Well No. **1**      in the

**SW<sub>1</sub>**      Company or Operator      Lease      **21-S**      R. **37-R**      N. M. P. M.,  
**Drinkard**      of Sec. **21**      T.      **Lea, New Mexico**      County.

The dates of this work were as follows: **December 31, 1951**

Notice of intention to do the work was ~~submitted~~ submitted on Form C-102 on **December 29, 1951** 19  
and approval of the proposed plan was ~~was not~~ obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Set 3876' of 5½" OD, Grade J-55, 17#, casing liner at 6512' in 6-3/4" hole hanging top of liner at 2636' in 8-5/8" OD casing with Brown Well Service packer and setting tool. Baker 5½" float collar, shoe and 2 - 5½" Baker centralizers was used and cement was circulated. Cement was allowed to set 48 hours before drilling plug, and casing and cement was tested with 1200# pressure.

Witnessed by **Piner Wardlaw**      **E. F. Moran, Inc.**      **Toolpusher**  
Name      Company      Title

Subscribed and sworn before me this.....

**3 rd** day of **January**, 19 **52**

*[Signature]*  
Notary Public

I hereby swear or affirm that the information given above is true and correct.

Name *[Signature]*

Position **Agent**

Representing **Ross Sears**  
Company or Operator

My Commission Expires June 10, 1953

My commission expires.....

Address **Artesia, New Mexico**

Remarks:

APPROVED

Date **JAN 7 1952**

*[Signature]*  
Name  
Title