

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

RECEIVED

DEC 2 1951

OIL CONSERVATION COMMISSION

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

| | | | |
|--|----------|--|--|
| REPORT ON BEGINNING DRILLING OPERATIONS | | REPORT ON REPAIRING WELL | |
| REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL | | REPORT ON PULLING OR OTHERWISE ALTERING CASING | |
| REPORT ON RESULT OF TEST OF CASING SHUT-OFF | X | REPORT ON DEEPENING WELL | |
| REPORT ON RESULT OF PLUGGING OF WELL | | | |

November 30, 1951

Hobbs, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____

Ross Sears _____ Wants _____ Well No. 1 _____ in the _____
Company or Operator _____ Lease _____
SW _____ of Sec. 21 _____, T. 21S _____, R. 37E _____, N. M. P. M.,
Drinkard _____ Field, Lea, New Mexico _____ County.

The dates of this work were as follows: November 28, 1951

Notice of intention to do the work ~~was~~ ^{was} ~~submitted~~ ^{submitted} on Form C-102 on November 26 _____ 19 51
and approval of the proposed plan was ~~obtained~~ ^{obtained}. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Set 13-3/8" New, 48#, Range 2, Naylor Spiral Weld Casing at 163' in 17 1/2" hole, using 150 sacks regular cement. On November 29, 1951, 13-3/8" casing was re-cemented with 96 sacks of regular cement which was circulated to the surface. Cement was allowed to set 32 hours and casing and cement was tested with 300# pressure before and after drilling plug on November 30, 1951.

Witnessed by Piner Wardlaw _____ E. F. Moran, Inc. _____ Toolpusher _____
Name _____ Company _____ Title _____

Subscribed and sworn before me this 24th _____
day of December 1951
P. E. Bashin _____
Notary Public

I hereby swear or affirm that the information given above is true and correct.
Name J. P. Moran _____
Position Agent _____
Representing Ross Sears _____
Company or Operator _____

My commission expires June 10, 1953 Address Artesia, New Mexico

Remarks:

Ray Yarbrough _____
Name _____
Oil & Gas Inspector Title _____