

OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

Miscellaneous Reports on Wells

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<input checked="" type="checkbox"/>	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

December 7, 1951

Hobbs, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the.....

Ross Sears Wants Well No. 1 in the
Company or Operator Lease
Salt of Sec. 21, T. 21S, R. 37E, N. M. P. M.,
Drinkard Field Lee, New Mexico County.

The dates of this work were as follows: December 4, 1951

Notice of intention to do the work ~~was~~ ^{was} submitted on Form C-102 on December 2 1951
~~and~~ and approval of the proposed plan was ~~(was not)~~ obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Run 84 joints of 8-5/8" OD, 28#, H-40, new casing using 8-5/8" OD Baker Cement Guide Shoe, 3-5/8" OD Larkin Double Female Float Collar, and 2 - 8-5/8" OD Baker Model G-20 Casing Centralizers, and cemented at 2735' with 1000 sacks 8% gel and 200 sacks regular cement (total 1200 sacks), circulated cement. Plug down at 10:40 PM December 4, 1951. Cement was allowed to set 48 hours and casing and cement was tested with 1000# pressure.

Witnessed by Piner Wardlaw E. F. Moran, Inc. Toolpusher
Name Company Title

Subscribed and sworn before me this 24th

day of December, 1951

D. B. Gashin

Notary Public

I hereby swear or affirm that the information given above is true and correct.

Name J. P. Gashin

Position Agent

Representing Ross Sears
Company or Operator

My commission expires June 10, 1953

Address Artesia, New Mexico

Remarks:

Ray Garbrough
Name
Oil & Gas Inspector
Title