

NEW MEXICO OIL CONSERVATION COMMISSION

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission District Office within ten days after the work specified is completed. It should be signed and filed as a report on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<input checked="" type="checkbox"/>	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

February 14, 1952

Hobbs, New Mexico

Date

Place

Following is a report on the work done and the results obtained under the heading noted above at the.....

Ross Sears Company or Operator **Wants** Lease Well No. **2** in the
SE-1 of Sec. **21**, T. **21**, R. **37**, N. M. P. M.,
Drinkard Pool **Lea, New Mexico** County.

The dates of this work were as follows: **January 10 & 11, 1952**

Notice of intention to do the work was (~~written~~) submitted on Form C-102 on **January 8, 1952**, 19.....
 and approval of the proposed plan was (~~written~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Set 5½" OD, 17#, Grade J-55, Range 2, L/T&C, 3rd Tnd., 56 joints Spang and 145 joints National Seamless casing, at 6495' in 6 3/4" hole using Baker Guide Shoe and Float Collar and 3 Larkin Centralizers. Casing was cemented with 300 sacks El Toro Regular Cement Feb. 11, 1952 1:50 A.M., pump and plug method. Cement was allowed to set 52 hours before drilling plug Feb. 13, 1952 @ 6:00 A.M. and cement and casing was tested w/ 1200# pressure. Temperature Survey Feb. 11, 1952 showed top of cement outside 5½" OD casing to be 3225'.

Witnessed by **C. H. Huff** Name **E. F. Moran, Inc.** Company **Toolpusher** Title

APPROVED:
OIL CONSERVATION COMMISSION

Ray Yankrough
Oil & Gas Inspector
Name
Title

FEB 20 1952

Date

19

I hereby swear or affirm that the information given above is true and correct.

Name **J. W. Rodgen**
Position **Agent**

Representing **Ross Sears**
Company or Operator

Address **Artesia, New Mexico**