

Page No. 3

Well Name ELLIOTT A#3

DATE: Cont.

2-4-95 From 4572' to 3000' - PUH w/ O.E. 2 3/8" Tbg. to 3150' (150' below 5 1/2" Csg. Stub) R.U. HOWCO + Spot 100 sx. Class "C" Cnt. w/ 2% CaCl₂. Mixed @ 14.8ppg + 1.32 Yield. Balanced Plug from 3150' up to + 2750' - POH w/ 2 3/8" Prod. Tbg. - WOC 2 hrs. - RIH w/ O.E. 2 3/8" Tbg. Tag hard Cnt. @ 2902' - R.U. HOWCO + Spot 100 sx. Class "C" Cnt. w/ 2% CaCl₂, Mixed @ 14.8ppg, + 1.32 Yield. Balanced Plug from 2902' up to + 2604' - PUH to 2600'. R.U. HOWCO + Test 9 5/8" Csg. from 2600' to Surface to 500 psi. - Held OK, w/ No leak off. - Continue to Circ. 9 5/8" Csg. Capacity w/ 208 bbls 10*/gel B.W. w/ 14.4*/bbl. Salt Gel. from 2600' to Surface. - POH w/ 2 3/8" Tbg. R.U. Apollo W.L. + Perf. 9 5/8" Csg. 4" HSC Guns from 335' to 334' - 4 Total Holes. - R.D. W.L. + SION.

2-5-95 RIH w/ 2 3/8" O.E. Tbg. - Tag hard Cnt. @ 2652' (86 Jts.) POH Layind down 2 3/8" Tbg. - R.U. HOWCO + Cnt. down 9 5/8" Csg., thru 5gz. Holes @ 335', + up 9 5/8" X 13 3/8" Csg. Annulus w/ 360 sx. Class "C" Neat Cnt. mixed @ 14.8ppg + 1.32 Yield. - Circ. approx. 20 sx. Cnt. to p.i.t. Cnt. @ Surface inside 9 5/8" + 9 5/8" X 13 3/8" Annulus. R.D. HOWCO. - N.D. BOP, N.D. 9 5/8" Csg. head. - Shut down.