

APPROVED


Form 9-331a
(Feb. 1961)

* SUBJECT TO REGULATION

APR 24 1963 (SUBMIT IN TRIPLICATE)

Budget Bureau No. 42-R358.4.
Form Approved.Land Office Las CrucesLease No. 032591a

Unit _____



E. G. HUBBLE UNITED STATES
ACTING DISTRICT ENGINEER DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

APR 24 1963

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

April 23, 1963

E. Elliott "A"

Well No. 3 is located 980 ft. from N line and 330 ft. from E line of sec. 21

SW 1/4 of NW 1/4 21 S 37 E 101 PM
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Here (at present) La New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 3446 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

1. Propose to pull rods and pump, install BOP's.
2. Run wireline gauge to 7325'. Run Baker Model 'B' CERP and set at 7320'. Test csg to 2500# for 30 min. Run GRN log from 7280 to 5000'.
3. Perf also section 3/2 bullets/ft (Est. 15-2 ft sections) from 7188 to 7220, test tbgs to 6000# and BOP's to 2000#. Acidize w/15,000 gal MIBS using 60 BBS.
4. Pull tbgs and tbgs tester and Baker CB. Run tbgs rods and test well on pump. Potential well for state allowable.

Abandon M&K as it has reached its economic limit.

- * The setting of a bridge plug does not constitute permanent abandonment of the lower perforations. Should conditions warrant, at the time of permanent abandonment, the bridge plug must be drilled out and cement placed across all perforations.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Sunray Oil CompanyAddress P. O. Box 125
Hobbs, New MexicoBy [Signature]
Title District Engineer