NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is no begin. A 30py will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

OTICE OF INTENTION O CHANGE PLANS		Notice by Checking Below		
	Notice of Intentic Temporarily Aban		otice of Intention Drill Deeper	
OTICE OF INTENTION PLUG WELL	Notice of Intention to Plug Back	1 3	otice of Intention Set Liner	
OTIGE OF INTENTION SQUEEZE	Notice of Intention to Acidize		otice of Intention Shoot (Nitro)	
TICE OF INTENTION GUN PERFORATE	Notice of Intentic (Other)	· · · · · · · · · · · · · · · · · · ·	otice of Intention Other)	
L CONSERVATION COMMISSION OF THE PROPERTY OF T	ON Hobbs, No.		September 5, 1961	<u> </u>
ntlemen:		(Place)	(Date)	
Following is a Notice of Intention Dalf Oil Corporation				
SW (Company or O	22ªtor) 21-6	3 /28	Noinin	(Unit)
(40-acre Subdivision) 4 of Sec	, T	., RNMPM.,		Poo!
at 7" on g. at approx.	2800' & 9-5/8" es e fellowing interva	g. at approx 1590		s fellow:
pot ement plugs in the pot ement plugs in the PMTD - 3615' (7" esg. Apprex 2850-2750' (to Apprex 1640-1540' (to 1300-1200' (top salt 50-0' (top surface es leen lecation, salvage es Shell 041 Co.	e following interval. perfs) op 7" esg. stub). op 9-5/8" esg. stub & enhydrite). 3/8" surf easing.) asing). surface equipment hie Oil Go.	g. at approx 1590° als: b). d install 4° x 4° m Tidewater 011 Go.	and pull es g. arker Markham, Come, &	a Redfern
out 7" es g. at apprex. pot coment plugs in the a. PED - 3615' (7" esg. b. Apprex 2850-2750' (to c. Apprex 1640-1540' (to c. 1300-1200' (top salt c. 50-0' (top surface est lean location, salvage es: Shell Gil Go. Box 1597 Hobbs, New Max.	e following interval. perfs) op 7" esg. stub). op 9-5/8" esg. stub à embydrite). 3/8" surf easing.) asing). surface equipment hie Oil Go. ex 2107 obbs, New Mex.	g. at approx 1590' als: b). & install 4' x 4" m Tidewater Oil Go. Box 547 Hobbs, New Mexico	arker Markham, Cone, & 1706 Gr. Flains Lubbook, Texas	a Redfern
out 7" es g. at approx. opt coment plugs in the l. PRED - 3615' (7" esg. l. Approx 2890-2750' (to l. 1300-1200' (top salt l. 350-258' (bettem 13-) l. 50-0' (top surface es lean location, salvage es Shall Q11 Co. Bex 1997 Hobbs, New Mex. Reproved.	e following interval. perfs) op 7" esg. stub). op 9-5/8" esg. stub à embydrite). 3/8" surf easing.) asing). surface equipment hie Oil Go. ex 2107 obbs, New Mex.	g. at approx 1590' als: b). & install 4' x 4" m Tidewater Oil Co. Box 547 Hobbs, New Mexico GULF OIL CORPORA	arker Markham, Cone, & 1706 Gr. Flains Lubbook, Texas	a Redfern
Bez 1997 Be	e fellowing interval. perfs) op 7" esg. stub). op 9-5/8" esg. stub à anhydrite). 3/8" surf easing.) asing). surface equipment hie Oil Go. ex 2107 obbs, How Mex.	g. at approx 1590' als: b). & install 4' x 4" m Tidewater Oil Co. Box 547 Hebbs, New Mexico GULF OIL CORPORA AREA PRODUCTION By	and pull es g. arker Markham, Cone, & 1706 Gr. Flains Labbook, Texas FIGS Company of Operator MANAGER unications regarding well to	Redfern Life Mile

Address