

# OIL CONSERVATION COMMISSION

## SANTA FE, NEW MEXICO

### Miscellaneous Reports on Wells

MAR 22 1951  
OIL CONSERVATION COMMISSION  
HOBBS-OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	X	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

3-21-51

Hobbs, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO.  
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the \_\_\_\_\_  
Shell Oil Company Argo "A" Well No. 8 in the \_\_\_\_\_

\_\_\_\_\_ of Sec. 22, T. 21-S, R. 37-E, N. M. P. M.,  
NW/4 \_\_\_\_\_  
Brunson Field Lea County.

The dates of this work were as follows: 3-19 & 3-20-51

Notice of intention to do the work was (~~submitted~~) submitted on Form C-102 on 3-19 19 51

and approval of the proposed plan was (~~obtained~~) obtained. (Cross out incorrect words.)

#### DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

After WOC 36 hrs. tested casing w/600 psi. Pressure bled to 100 psi. in 30 min. Found top cement @ 2860' & drilled to 2915' (10' above shoe). Tested casing w/600 psi. Pressure bled to 100 psi. in 30 min. Ran Baker retrievable cementer & tested sections of hole. Leak in casing found @ 930 to 935'. Spotted 15 sack neat cement opposite casing leak with open-ended drill pipe. Squeezed w/600 psi. for 30 min. After WOC 8 hrs. drilled plug and tested casing w/700 psi. for 30 min. Test O.K.

Witnessed by R. F. Gorman Shell Oil Company Mechanical Engineer  
 Name Company Title

Subscribed and sworn before me this \_\_\_\_\_

21st day of March, 19 51

*[Signature]*  
 Notary Public

I hereby swear or affirm that the information given above is true and correct.

Name L. E. Slagle *[Signature]*

Position Division Mechanical Engineer

Representing Shell Oil Company  
 Company or Operator

My commission expires My Commission Expires Sept. 16, 1954 Address Box 1457, Hobbs, New Mexico

Remarks:

APPROVED  
 Date MAR 22 1951

*[Signature]*  
 Oil & Gas Inspector  
 Title