~	-24 4	ł	ţ.	1	·	
1999 - 1999 1999 - 1999	1.000	57.5				
ALC: NO. OF THE PARTY NAME	i i	ſ				
į			·••••	·a •***	. •	

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

## Indicate Nature of Notice by Checking Below

Notice of Intention to Change Plans	NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		Notice of Intention to Drill Deeper	
Notice of Intention to Plug Well	Notice of Intention to Plug Back	x	Notice of Intention to Set Liner	
Notice of Intention to Squeeze	NOTICE OF INTENTION TO ACIDIZE		Notice of Intention to Shoot (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (Other)	

OIL CONSERVATION COMMISSION SANTA FE, NEW MEXICO

.....County.

Hobbs, New Mexico

February 1, 1956

Gentlemen:

1.6

Following is a Notice of Intention to do certain work as described below at the.....

Shell Oil Company	Turner	Well No 11	. <b>#N#</b>
(Company or Operator)		Well No	
SE 1/4 SW 1/4 of Sec. 22, T	1-9 R-37-E NMPM.	Brunson	Peol

## FULL DETAILS OF PROPOSED PLAN OF WORK

(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

We propose to plug back from 7783' in the Brunson (Ellenburger) Pay Zone and recomplete as a Connell sand (Hare Field) producer as following:

- (1) Pull tubing and run radioactivity survey
- (2) Set cast iron bridging plug at 7465' and cap with cement
- (3) Lead hole with oil and perforate 5-1/2" casing from 7435' to 7450' w/4 bullet shots per foot.
- (4) Run tubing with packer and swab test. Wash perforations with 500 gallons MCA. Set packer and treat with 1000 gallons MCA soak 6-8 hours and swab load.
- (5) Swab test
- (6) Pull tubing and treat via casing with 20,000 gallons refined oil containing 1 1/2# sand/gallon. Overflush with 150 barrels oil.
- (7) Run tubing and swab lead. If results are satisfactory, place on production.

Approved	Shell Oil Company
Except as follows:	Company or Operator Original signed by By
	Position Mechanical Engineer
Approved OIL CONSERVATION COMMISSION	Send Communications regarding well to:
By M. Duly	NameShell Oil Company
Title	Address. Box 1957 - Hobbs, New Mexice