

Name THE [illegible]

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
NO SAMPLES TAKEN ABOVE 3000 FEET			
3000	5072	2072	Lime, dolomite, with some shale and anhydrite.
5072	5150	78	Dolomite
5150	5535	385	Sandy dolomite
5535	7355	1820	Lime, dolomite, shale, some anhydrite
7355	7398	43	Detrital material
7398	7425	27	Shale
7425	7540	115	Sand and shale
7540	7580	40	Lime
7580	7735	155	Dolomite
7735	7758	23	Granite wash and granite
TD	7758		Granite
<u>SCHLUMBERGER TOPS:</u>			
Drinkard		6400'	(-2977')
Permian/Simpson contact		7398'	(-3975')
Ellenburger lime		7540'	(-4117')
Ellenburger dolomite		7580'	(-4157')
Granite.		7735'	(-4312')
DST: 7324-7524 (Simpson Sand)			5/8" BC & 1" TC on 3 1/2" DS. Tool open 90 min. Gas to surface in 8 min. Mud in 11 min. Oil in 20 min. Flowed 81.67 bbls. oil in 1 hour. GOR 305. Gravity 43° API. FBHP 2175 p.s.i. 15 min. SIBHP 2625 p.s.i. MCP 3650 p.s.i. <u>Positive Test.</u>