

NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

|   |   |  |   |   |  |
|---|---|--|---|---|--|
| NOTICE OF INTENTION<br>TO CHANGE PLANS  |   | NOTICE OF INTENTION TO<br>TEMPORARILY ABANDON WELL |   | NOTICE OF INTENTION<br>TO DRILL DEEPER  |  |
| NOTICE OF INTENTION<br>TO PLUG WELL     |   | NOTICE OF INTENTION<br>TO PLUG BACK                | X | NOTICE OF INTENTION<br>TO SET LINER     |  |
| NOTICE OF INTENTION<br>TO SQUEEZE       |   | NOTICE OF INTENTION<br>TO ACIDIZE                  | X | NOTICE OF INTENTION<br>TO SHOOT (Nitro) |  |
| NOTICE OF INTENTION<br>TO GUN PERFORATE | X | NOTICE OF INTENTION<br>(OTHER) SANDERAC            | X | NOTICE OF INTENTION<br>(OTHER)          |  |

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

Roswell, New Mexico

December 22, 1960

(Place)

(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Shell Oil Company Turner Well No. 16 in M  
(Company or Operator) Lessee (Unit)  
SW 1/4 SW 22 1/4 of Sec. 22, T. -21-S, R. -37-E, NMPM., Wanta-Abo Pool  
(40-acre Subdivision)  
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK

(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

RECOMPLETE FROM WANTZ-ABO TO BLINEBRY OIL

1. Set Model "N" CIBP @ 5950' & cap w/cement. Run cement bond log from PETD to top of liner.
2. If cement bond present, perforate at the following levels with the FI gun or 8-way frac jet: 5723', 5737', 5764', & 4778'.
3. Run 3" X-line frac tubing w/FBRC.
4. Wash and treat perforations w/500 gallons MCA.
5. Treat w/20,000 gallons lease oil + 1# 20-40 mesh sand/gallon admixed w/sufficient FLA to obtain a spurt loss less than 10 cc & 30-minute fluid loss less than 20 cc.
6. Test. Kill well (use oil base mud if necessary), pull 3" tubing & FBRC.
7. Rerun 2" tubing w/packer and place on production.

Approved....., 19.....  
Except as follows:

Shell Oil Company

Company or Operator

R. A. Lowery

Original Signed By

R. A. LOWERY

Position..... District Exploitation Engineer  
Send Communications regarding well to:

Approved  
OIL CONSERVATION COMMISSION

By.....

Title.....

Name..... Shell Oil Company

Address..... Box 845, Roswell, New Mexico