

OWWO
COUNTYLEA FIELD Undesignated STATE NM 16756

OPR SHELL OIL CO. MAP
16 Turner
Sec 22, T-21-S, R-37-E CO-ORD
330' FSL, 660' FWL of Sec

Re-Cmp 6-19-72	CLASS		EL	
	FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING				
13 3/8" at 208' w/150 sx				
8 5/8" at 2926' w/2350 sx				
5 1/2" at 7785' w/970 sx				
LOGS EL GR RA IND MC A				
	TD 7864'; PBD 4060'			

IP (San Andres) Perfs 4004-55' F 800 MCFGPD + 30 B cond Per day.
Pot based on 24 hr test thru 48/64" chk. Grav (gas) NR, (cond)
32.4

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. PROP DEPTH 5080' TYPE WO
DATE

F.R.G. 10-28-72; Opr's Elev. 3427' DF
PD 5080' WO (San Andres)
(Orig. comp 3-11-52 from OH 7785-7864', OTD 7864';
OWWO & Re-Cmp 7-4-59 thru (Abo) Perfs 7078-7244',
OPB 7245'; OWWO & Re-Cmp 11-20-59 thru (Abo)
Perfs 7020-7244', OPB 7245'; OWWO & Re-Cmp 1-10-61
thru (Blindbry) Perfs 5723-78', OPB 5950'; OWWO
& Re-Cmp 2-8-64 thru (Paddock) Perfs 5113-5168',
OPB 5640'; OWWO & Re-Cmp 7-22-65 as Water Supply
Well (San Andres) Perfs 4004-4818', OPB 5080')
10-23-72 TD 7864'; PBD 4060'; COMPLETE
PB to 4060'
No Additional Perfs or treatment
10-28-72 COMPLETION REPORTED

COUNTY	LEA	FIELD	Eunice	STATE	NM	OWWO
OPR	SHELL OIL COMPANY			MAP		
WS-16 Turner						
Sec. 22, T-21-S, R-37-E				CO-ORD		
330' fr S Line & 660' fr W Line of Sec.						
Re-Spd 6-16-65		CLASS		EL		
Re-Cmp 7-22-65		FORMATION	DATUM	FORMATION	DATUM	
CSG & SX - TUBING						
13 3/8" 208' 150						
8 5/8" 2926' 2350						
5 1/2" 7785' 970						
LOGS EL GR RA IND HC A						
		TD 7864'				

WATER SUPPLY WELL

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	PROP DEPTH	TYPE
DATE		

8-9-65 F.R.C. 8-12-65; OWWO
 Orig. comp from Paddock 5113-5168', OTD 7864'
 TD 7864', PBD 5080', COMPLETED
 Set CIBP @ 5080'
 Perf (San Andres) 4004-09', 4012-16', 4024-31',
 4036-42', 4050-55', 4073-77', 4086-90', 4234-
 44', 4249-59', 4265-75', 4279-4370', 4507-26',
 4554-70', 4574-88', 4594-4620', 4632-62',
 4676-4705', 4708-37', 4782-4818' W/2 SPF
 Ac. 15,500 gals.
 Flwd average 6000 BWPD + 2100 MCFGPD, FCP
 300#.
 Swab indicated gas entry from perfs 4004-90'.