NEW MEXICO OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of

NOTICE OF INTENTION TO TEST CASING		NOTICE OF INTENT	TON TO SHOOM OR	
SHUT-OFF	<u> </u>	CHEMICALLY	REAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS	-	NOTICE OF INTENT	FION TO PULL OR LTER CASING	
NOTICE OF INTENTION TO REPAIR WELL		NOTICE OF INTENT		LL -
NOTICE OF INTENTION TO DEEPEN WELL				
	Hobl	os, New Mexico	March 2,	1950
OIL CONSERVATION COMMISSION, Santa Fe, New Mexico.		Place	Date	
Gentlemen:				
Following is a notice of intention to do certain work	ുള ർക്ക	cribed below at the		
Shell Oil Company Sa Company or Operator Leas	rkey	tribed below at the	Wall No 4	. STE/h GT
of Sec. 23 , T. 21-S , R. 37-E	se		well No	in 52/4, 31
Lea County.	, N.	M. P. M.,D	rinkard	Field.
FULL DETAILS OF I				
Ran 13 3/8-inch casing and cemented down at 5:45 PM 3-1-50 Company	d at	229 feet with 27	5 sax regular.	Plug
Ran 13 3/8-inch casing and cemented down at 5:45 PM, 3-1-50. Cement concessing.	d at	229 feet with 27	5 sax regular.	Plug
Ran 13 3/8-inch casing and cemented down at 5:45 PM, 3-1-50. Cement co	d at	229 feet with 27	5 sax regular.	Plug
Ran 13 3/8-inch casing and cemented down at 5:45 PM, 3-1-50. Cement co	d at	229 feet with 27	5 sax regular.	Plug
Ran 13 3/8-inch casing and cemented down at 5:45 PM, 3-1-50. Cement co	d at	229 feet with 27	5 sax regular.	Plug
Ran 13 3/8-inch casing and cemented down at 5:45 PM, 3-1-50. Cement co	d at	229 feet with 27	5 sax regular.	Plug
Ran 13 3/8-inch casing and cemented down at 5:45 PM, 3-1-50. Cement co	d at	229 feet with 27	5 sax regular.	Plug
Ran 13 3/8-inch casing and cemented down at 5:45 PM, 3-1-50. Cement co	d at	229 feet with 279 ated. After 24 1	5 sax regular. hours WOC will	Plug
Ran 13 3/8-inch casing and cemented down at 5:45 PM, 3-1-50. Cement contains.	d at	229 feet with 279 ated. After 24 1	5 sax regular.	Plug
Ran 13 3/8-inch casing and cemented down at 5:45 PM, 3-1-50. Cement contains.	d at	Shell Oil Comp Frank R. L. Position District	Company any or Operator overing	Plug
Ran 13 3/8-inch casing and cemented down at 5:45 PM, 3-1-50. Cement contains.	d at	Shell Oil Comp Frank R. L. Position District	Company any or Operator overing Superintendent cations regarding we	Plug