Orig: & ec: OCC ec: VDA JTR

NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

	Indicate Nature of Re	eport by Checking	Below		
REPORT ON BEGINNING DRILLING OPERATIONS	REPORT ON RES		REPORT OF REPAIRING		
EPORT ON RESULT F PLUGGING WELL	REPORT ON REC	OMPLETION	REPORT Of (Other)	N	
	Fe (Dat	bruary 28, 1	953	Hebbs, New (Place)	(exice
Following is a report on the work done	e and the results obtaine	ed under the headir	ng noted above at the		
Sinclair Oil & Gas Company			Roy Barton		
(Company or Operator		•	(Lease)	1.0mm	•••
Milhean Drilling Company (Contractor)		, Well No	in the SK	1/4 NE 1/4 of Sec.	23
21S , R 37 E , NMPM.,	Wants-Abe	Pool,	Lea		County.
7993 py (cement inside	e or 3 T/S. cast	יש איין			
et 5 1/2" casing @ 7348° and et set 72 hours and perforat wabbed dry and acidised W/2	i cemented with ted W/620 jet sh ,000 gallons of	500 sacks of ots from 7,00 mud acid by	00 to 7,155. R	an 7151° of 2°	UE tub
et 5 1/2" casing @ 7348 and et set 72 hours and perforative bed dry and acidized W/2 lewed and swabbed 135 barrel	i cemented with ted W/620 jet sh ,000 gallons of ls of new oil an	500 sacks of ots from 7,00 mud acid by 1 d 36 barrels	00 to 7,155. Rivestern Co. of acid water	an 7151° of 2°	UE tub
et 5 1/2" easing @ 7348° and set set 72 hours and perforate wabbed dry and acidized W/2 lewed and swabbed 135 barrel	i cemented with ted W/620 jet sh ,000 gallons of ls of new oil an	500 sacks of ots from 7,00 mud acid by 1 d 36 barrels	00 to 7,155. R	an 7151° of 2°	UE tub
et 5 1/2" easing @ 7348 and et set 72 hours and perforat wabbed dry and acidized W/2, lewed and swabbed 135 barre. Vitnessed by	i cemented with ted W/620 jet sh ,000 gallons of ls of new oil an	500 sacks of ots from 7,00 mud acid by 1 d 36 barrels Sinclair Of (Company)	00 to 7,155. Rewestern Co. of acid water	in 12 hours. Foreman (Title)	
et 5 1/2" easing @ 7348 and set set 72 hours and perforate wabbed dry and acidized W/2 lewed and swabbed 135 barred vitnessed by George R. Huddle (Name) OIL CONSERVATION COM	i cemented with ted W/620 jet sh ,000 gallons of ls of new oil an	Sinclair Of (Company) I hereby certify to the best of m	that the information gry knowledge.	in 12 hours. Foreman (Title)	
et 5 1/2" easing @ 7348 and set set 72 hours and perforate sabbed dry and acidized W/2 lewed and swabbed 135 barred fitnessed by George R. Huddle (Name)	i cemented with ted W/620 jet sh ,000 gallons of ls of new oil an	Sinclair Of (Company) I hereby certify to the best of m Name	00 to 7,155. Rewestern Co. of acid water	in 12 hours. Foreman (Title) iven above is true and	